

POWER G-2000

Graffiti & Paint Remover

Form: Thickened Liquid

Color: Colorless to Slight Yellow

Odor: Mild

pH: N/A

Solubility (in water): Emulsifiable

VOC Content (% by weight): < 1.0%

Flash Point (ASTM D-7821): >200°F

Specific Gravity: 1.0 g/cm³

Density: 8.35 lbs/gal

<u>This Product Contains:</u>	<u>CAS #</u>
Water.....	7732-18-5
Dimethyl-2-methyl Glutarate	14035-94-0
Aliphatic Ethoxylated Alcohols	78330-20-8
Methyl Ester of Soybean Oil.....	67784-80-9
Ethoxyl-propoxyl Terpene	174955-61-4

Safe For Use On...

- Bathroom Partitions
- Phone Booths
- Counters
- Lamp Posts
- Bus Stops & Seats
- Stainless Steel
- Aluminum Siding
- Road Signs
- Desks
- Trains
- Wall Tile
- Lockers
- Glass

Almost Any Hard Surface!

DIRECTIONS FOR USE: Spray graffiti with POWER G-2000 and lightly scrub in a circular motion. Rinse paint and graffiti residue with water. For porous surfaces, such as concrete and brick, saturate area with POWER G-2000 and let work for several minutes. Rinse paint and ink residue with a high pressure water rinse. Repeat these steps if necessary. As with any graffiti and paint, the longer it stays on the surface the harder it is to remove. POWER G-2000 works best if graffiti and paint is not allowed to cure more than 24 hours.

NOTE: When using POWER G-2000 on a pre-painted surface, initially test in an inconspicuous area to make sure paint is not removed along with the graffiti. POWER G-2000 may attack certain plastics.

HMIS®			NFPA®		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	1
Flammability.....	Moderate	2	Moderate	Flammability.....	1
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None