



RUST CONVERTER

POLYMERIC RUST TRANSFORMER

STOPS, CONVERTS, AND INHIBITS RUST

- STOPS THE SPREAD OF RUST • CONVERTS RUST TO A PAINTABLE SURFACE
- PROTECTS AGAINST FUTURE CORROSION • NON-FUMING

WARNING:

May cause damage to organs (liver) through prolonged or repeated exposure.

KEEP OUT OF REACH OF CHILDREN

Net Contents: 1 5 20 35 55 Gallon(s)

RUST CONVERTER

POLYMERIC RUST TRANSFORMER



P.O. BOX 245013
MILWAUKEE, WI 53224
800.776.7192
WWW.SHARECORP.COM



Wear eye protection, protective clothing, protective gloves.
Get medical advice/attention if you feel unwell.

Dispose of contents/container to comply with local/regional/national/international regulations.

For industrial and commercial use only.

For additional information, see Safety Data Sheet

WARNING:

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

This new surface conditioner and primer changes rust into a dark protective polymeric coating. It converts existing rust to an inert coating that seals out moisture to prevent future rust and corrosion. This rust converter provides an excellent primer coating for the application of quality oil-based paints. Surfaces protected with this primer and an oil-based paint system resists the effects of weather, rain, sun and salt spray without peeling or cracking. This easy-to-use product is the first step in providing long-term protection of steel and iron surfaces.

DIRECTIONS FOR USE

SURFACE PREPARATION: Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease.

APPLICATION: SHAKE OR STIR WELL BEFORE USING! Apply this product using a brush or roller. This product is ready-to-use – NO thinning is required.

COVERAGE: 500 square feet per gallon on a smooth, non-porous surface. Irregular, porous or textured surfaces may require more product.

DRYING TIME: The resulting coat will dry to a smooth, dark finish in 20 minutes. Apply a second coat to ensure complete transformation of rusty surfaces. Allow 48 hours of cure time before the application of the finished paint coat.

For long-lasting protection of iron surfaces, the cured rust converter coating should be sealed with two coats of a high quality oil-based paint. No other primer is required.

CLEAN-UP: Application equipment should be cleaned immediately with soap and water.

GENERAL: Do not apply this product if the surface temperatures are below 50°F. Store in a cool, dry place, protected from freezing or temperatures above 100°F.

IMPORTANT:

DO NOT RETURN UNUSED MATERIAL TO ORIGINAL CONTAINERS.

NFPA® Ratings

Health: 2; Flammability: 0; Reactivity: 0

Contains/CAS Number:

Water/7732-18-5; Proprietary Polymer/Proprietary;
2 butoxyethanol/1111-76-2; Tannic Acid/1401-55-4;
Oxalic Acid/6153-56-6



Please Recycle.

0346.012015