

RELEASE EASE

Asphalt Release Agent

Form: Clear Liquid

Color: Yellow

Odor: Slight Solvent / Oil

pH: 10.50 – 11.00

Solubility (in water): Soluble
(in mineral spirits): Insoluble

Viscosity (CPS at 70°F): >40

Flash Point (ASTM D-7821): N/A

Specific Gravity: 1.04 ± 0.05 g/cm³

Density: 8.68 ± 0.05 lbs/gal

Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Water.....	7732-18-5
Tall Oil.....	8002-26-4
Tetrasodium EDTA.....	64-02-8
Potassium Hydroxide.....	1310-58-3

Uses...
• Truck Bed Coating
• Tool & Equipment Coating
• Snow Plow Coating
• Anti-Graffiti Coating
• Form Release Agent

DIRECTIONS:

RELEASE EASE is easy to use. Simply mix 1-1/2 quarts of RELEASE EASE in 2 gallons of water. Spray equipment thoroughly with solution. Agitate solution before and several times during use. Allow treated equipment to dry before putting into service. For optimum performance, equipment should be treated before each use.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health	1
Flammability	Moderate	2	Moderate	Flammability	0
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None