

AR-CHEM AG SLICK SHOT

Prohibits Residue Adhesion

Form: Liquid

Color: Clear, colorless

Odor: Lemon

pH: No data available

Solubility (in water): Insoluble
(in mineral spirits): Soluble

VOC Content (% by weight): >90.0

Flash Point (Closed Cup): 103°F

Specific Gravity: 0.79 g/ml

Density: 6.50 lbs/gal

Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Distillates (Petroleum), Hydrotreated Light	64742-47-8
Polydimethylsilicone.....	63148-62-9
Mixed Xylenes	1330-20-7
Cumene	98-82-8
Fragrance.....	Mixture

Other Uses...
• Brick Protector
• Wall Coating
• Graffiti Inhibitor
• Water proofer
• Reflective Sign Coating
• Asphalt Release Agent
• Concrete Truck Protector

DIRECTIONS: Apply with a sprayer, paint roller, or brush. For best results and longer life, wash the vehicle first, then rinse and allow to dry before applying AR-CHEM AG SLICK SHOT.

Two light coats (allowing at least an hour of drying time between applications) will provide good protection and will prevent unwanted deposits from adhering to equipment surfaces, allowing for faster and easier equipment clean up.

HMIS®			NFPA®		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	2
Flammability.....	Moderate	2	Moderate	Flammability.....	2
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None