



Earth's Own

SOY SLIDE

ALL NATURAL, BIODEGRADABLE RELEASE AGENT

INHIBITS ADHESION TO TRUCKBEDS AND OTHER EQUIPMENT

EASY TO APPLY • EASY ON THE ENVIRONMENT

DANGER

Causes serious eye damage

KEEP OUT OF REACH OF CHILDREN

Net Contents: 1 □ 5 □ 20 □ 35 □ 55 □ Gallons

Earth's Own

SOY SLIDE



P.O. BOX 245013

MILWAUKEE, WI 53224

800.776.7192

WWW.SHARECORP.COM



DANGER:

Causes serious eye damage.

PREVENTION:

Wear eye protection, protective clothing, protective gloves.

RESPONSE:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

DISPOSAL:

Offer empty container for recycling. If recycling is not available, discard container in trash.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

NFPA® RATINGS:

Health: 2; Flammability: 1; Reactivity: 0

INGREDIENTS/CAS#:

Methyl Ester of Soybean Oil (67784-80-9); Linear Alcohol Ethoxylate (34398-01-1); 1-Undecanol (112-42-5); Proprietary Fragrance (Mixture).

KEEP OUT OF REACH OF CHILDREN

Earth's Own SOY SLIDE

EARTH'S OWN SOY SLIDE is an specialized release coating that provides a molecular film that prevents the sticking and adhesion of materials to truck beds, molds and other equipment. **EARTH'S OWN SOY SLIDE** produces a thin heat resistant shield that provides a "slick" surface so that even sticky loads simply roll off. **EARTH'S OWN SOY SLIDE** also provides protection for your equipment surfaces, from deposits and from the damaging effects of rust and corrosion.

DIRECTIONS:

EARTH'S OWN SOY SLIDE is easy to use. Simply mix 1 part **EARTH'S OWN SOY SLIDE** to 6 parts of water for thicker, longer lasting coating. Mix 1 part **EARTH'S OWN SOY SLIDE** to 10 parts water for thinner, more economical coating. Simply spray equipment thoroughly with solution. Allow 15 minutes for molecular film to set before putting into service. For best performance, recoat equipment periodically during use. Use care when using **EARTH'S OWN SOY SLIDE** around synthetic surfaces (rubber, painted surfaces and certain plastics) that may be damaged by solvents.



Please Recycle.

0476.052215