

SOY SLIDE

All Natural, Biodegradable Release Agent



Form: Liquid

Color: Clear

Odor: Apple

pH: N/A

Solubility (in water): Emulsifiable
(in mineral spirits): Soluble

Viscosity (CPS at 70°F): >40

Flash Point (ASTM D-7821): >300°F

Specific Gravity: 0.88 ± 0.05 g/cm³

Density: 7.34 ± 0.05 lbs/gal

VOC Content (% by wt): 5.00-15.00

Ingredients

	<u>C.A.S. #</u>
Methyl Ester of Soy Oil.....	67784-80-9
Linear Alcohol Ethoxylate.....	34398-01-1
Green Apple Perfume	No CAS #

Use SOY SLIDE For:
• Truck Bed Coating
• Tool & Equipment Coating
• Anti-Graffiti Coating
• Form Release Agent
• Snow Plow Coating

DIRECTIONS: EARTH'S OWN - SOY SLIDE is easy to use. Simply mix 1 part of SOY SLIDE to 6 parts of water for thicker, longer lasting coating. Mix 1 part SOY SLIDE to 10 parts water for thinner, more economical coating. Simply spray equipment thoroughly with solution. Allow 15 minutes for molecular film to set before putting into service. For best performance, recoat equipment periodically during use. Use care when using SOY SLIDE around synthetic surfaces (rubber, painted surfaces, and certain plastics) that may be damaged by solvents.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health	0
Flammability	Moderate	2	Moderate	Flammability.....	1
Reactivity	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None