

SEWER COMPOUND XXX

Extra Strength Municipal Sewer Cleaner

Form: Pellets

Color: Red

Odor: None

pH: 14.00

Solubility (in water): Complete
(in mineral spirits): Insoluble

VOC Content (% by weight): None

Flash Point (ASTM D-7821): None

Specific Gravity: N/D

Density: N/D

Storage Stability (at 70°F): 1 year

Ingredients

	<u>C.A.S. #</u>
Sodium Hydroxide.....	1310-73-2
Sodium Nitrate.....	7631-99-4
Aluminum Granules	No CAS #
Dye	No CAS #

Good For...	
•	Animal Fats
•	Vegetable Fats
•	Oil
•	Hair
•	Paper
•	Organic Matter

DIRECTIONS: For Municipal Use - Pour or shovel about 25 pounds of SEWER COMPOUND XXX into manholes upstream and closest to the obstruction. A second addition following the first by 10-15 minutes may be necessary to remove more difficult obstructions. **For Industrial Use** - Use 1 or 2 pounds of SEWER COMPOUND XXX in normal drains. In food plants (such as packing houses, processing plants, and canneries where accumulations of organic matter are particularly high) 10 to 20 pounds may be required.

Always remove as much standing water in manholes, catch basins, and sewers as possible before adding SEWER COMPOUND XXX. Add product SLOWLY and carefully. NEVER USE A PLUNGER WITH THIS PRODUCT. NEVER USE HOT WATER. USE OF SEWER COMPOUND XXX GENERATES CONSIDERABLE HEAT WHICH MAY CAUSE ERUPTION OF DRAIN CONTENTS. IF POSSIBLE, PLACE A BUCKET OR OTHER DEEP CONTAINER OVER DRAIN OPENING AFTER TREATING. NEVER LOOK INTO DRAIN AFTER TREATING. Do not use in combination with or directly after treatment with acid type drain openers - SEWER COMPOUND XXX will react violently or explosively with acid drain opener products. Do not enter treated sewers until they have been thoroughly flushed with water.

CONSULT PRODUCT LABEL FOR DETAILED USE DIRECTIONS.

HMIS			NFPA		
Health.....	3	Severe 4	Extreme	Health	3
Flammability	0	Serious 3	High	Flammability	0
Reactivity	2	Moderate 2	Moderate	Reactivity	2
Personal Protection	X	Slight 1	Slight	Special Precautions.....	None
		Minimal 0	Insignificant		