



TANK PROTECTOR

WATER STORAGE RUST & CORROSION PREVENTATIVE

DANGER

Causes skin irritation.
Causes serious eye damage.

KEEP OUT OF REACH OF CHILDREN

Net Contents: 1 □ 5 □ 20 □ 35 □ 55 □ Gallons

SPECIMEN LABEL

TANK PROTECTOR



P.O. Box 245013
Milwaukee, WI 53224
800.776.7192
www.sharecorp.com

DANGER:

Causes skin irritation. Causes serious eye damage.

PREVENTION:

Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash before reuse.

IF ON SKIN: Wash with plenty of water.

If skin irritation occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

DISPOSAL: Offer empty container for recycling. If recycling is not available, discard container in trash.



Please Recycle.



TANK PROTECTOR inhibits rust and corrosion formation in all metal water tanks. Designed for fire departments, utilities, industrial and municipal storage tanks, laundry and hotel water storage systems, and emergency water supply facilities. **TANK PROTECTOR** forms a thin protective film on all exposed metal surfaces. It is non-toxic, odorless, tasteless, and protects all metals, including iron, steel, galvanized, brass, bronze, copper, and alloys. **TANK PROTECTOR** leaves no toxic residue, and treated tanks may be used for potable water without rinsing.

DIRECTIONS:

In fire trucks, emergency storage tanks, back pack sprayers and holding tanks, add 1 gallon of **TANK PROTECTOR** for each 1000 gallons of water. Treat with **TANK PROTECTOR** every time tank is filled. In flowing systems, inject or meter 3 gallons of **TANK PROTECTOR** per 10,000 gallons of water. After a 6 to 8 week initial treatment period, decrease the feed rate to 1 gallon per 10,000.

NFPA® RATINGS

Health: 2; Flammability: 0; Reactivity: 0

INGREDIENTS/CAS #:

Water (7732-18-5); Sodium Silicate (1344-09-8).

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

0627.051115