



# DIESEL KLEAN

## MULTI-FUNCTIONAL DIESEL FUEL ADDITIVE

THIS DIESEL FUEL ADDITIVE COMPLIES WITH THE  
FEDERAL LOW SULFUR CONTENT  
REQUIREMENTS FOR USE IN DIESEL  
MOTOR VEHICLES AND NON-ROAD ENGINES.

### DANGER

Flammable liquid and vapour. Harmful if swallowed or if inhaled.  
May be fatal if swallowed and enters airways.

Causes skin irritation. Causes eye irritation.

May cause respiratory irritation. May cause drowsiness or dizziness.

May cause genetic defects. • May cause cancer.

## KEEP OUT OF REACH OF CHILDREN

Net Contents: 12 Oz.



Please Recycle.

0657.050815

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com



### DANGER:

Flammable liquid and vapour. Harmful if swallowed or if inhaled. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer.

### PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, open flames, sparks. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing fume, mist, spray, vapours. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash before reuse.

**IF SWALLOWED:** Immediately call a doctor, a POISON CENTER. Rinse mouth. Do NOT induce vomiting.

**IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing.

Rinse skin with water/shower.

**If skin irritation occurs:** Get medical advice/attention.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

**If eye irritation persists:** Get medical advice/attention.

**If exposed or concerned:** Get medical advice/attention.

Call a doctor, a POISON CENTER if you feel unwell.

**In case of fire:** Use carbon dioxide (CO<sub>2</sub>), dry extinguishing powder, foam to extinguish.

**DIESEL KLEAN** is an anti-pollution formulation specifically developed for effective control of black and white exhaust emissions. It will eliminate moisture in diesel tanks, diesel lines and diesel storage tanks. It prevents fuel cracking, improves combustion and reduces or eliminates carbon build-up and varnish deposits. The results are increased mileage, decreased exhaust emissions, longer injector life and reduced maintenance costs.

**DIRECTIONS:** Add 1 pint of **DIESEL KLEAN** to 25 gallons of diesel fuel or 1 gallon to 200 gallons of diesel fuel.

### NFPA® RATINGS

Health: 2; Flammability: 2; Reactivity: 0

### INGREDIENTS/CAS #:

Solvent Naphtha (Petroleum), Light Aromatic (64742-95-6); Trimethylbenzene (25551-13-7); 1,2,4-Trimethylbenzene (95-63-6); 2-Ethylhexyl Nitrate (27247-96-7); Cumene (98-82-8); Mixed Xylenes (1330-20-7); Heavy Aromatic Naphtha (64742-94-5); Cymenes (25155-15-1)

*For industrial and commercial use only.*

*For additional information, see Safety Data Sheet.*

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Dispose of contents/container to comply with local/regional/national/international regulations.

**WARNING:** This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.