

# PRO DIESEL

## DIESEL FUEL PERFORMANCE CONDITIONER

**Form:** Liquid

**Color:** Amber

**Odor:** Petroleum-like

**pH:** No data available.

**Solubility (in water):** Insoluble

**Flash Point (ASTM D-7821):** > 115°F

**Density:** 0.91 g/mL

**Storage Stability (at 70°F):** 1 year

**This Product Contains:** **CAS#**

Solvent naptha, petroleum, light arom.	64742-95-6
2-Ethylhexyl nitrate	27247-96-7
Solvent naptha, petroleum, heavy arom.	64742-94-5
1,2,4-Trimethylbenzene	95-63-6
2-Butoxyethanol	111-76-2

### Great For Use In...

- Diesel Engines
- Over-The-Road Rigs
- Delivery Trucks
- Construction Equipment
- Farm Equipment
- Pick-up Trucks
- Stationary Diesel Engines

**Directions for Use:** **BULK STORAGE TANK:** Normal Operation, Add 1 Gallon of **PRO DIESEL** to 2,000 gallons of Diesel Fuel. **Cold Weather Operation,** Add 1 gallon of **PRO DIESEL** to 1,000 gallons of Diesel Fuel. Add directly to Storage Tank. **VEHICLE OR MACHINE FUEL TANK:** Normal Operation, Add 1 Quart of **PRO DIESEL** to 250 to 450 gallons of Diesel Fuel. Cold Weather Operation, Add 1 Quart of **PRO DIESEL** to 150 to 250 gallons of Diesel Fuel. Add directly to Fuel Tank. **Use in ULSD Blends up to B20.**

#### CONSULT PRODUCT LABEL FOR DETAILED DIRECTIONS

HMIS			NFPA		
	Severe	4	Extreme		
Health.....	Serious	3	High	Health.....	1
Flammability.....	Moderate	2	Moderate	Flammability.....	0
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None