



Transmission & Aluminum Cleaner

SPRAY CABINET CLEANER

DISSOLVES QUICKLY AND COMPLETELY
NON-FLAMMABLE • WATER SOLUBLE

WARNING

HARMFUL IF SWALLOWED.


Eye irritant. See side panel for further cautions and first aid instructions.

KEEP OUT OF REACH OF CHILDREN

Net Contents: 25 50 100 Pounds

Transmission & Aluminum Cleaner

SPRAY CABINET CLEANER



P.O. Box 245013
Milwaukee, WI 53224
(800) 776-7192
www.sharecorp.com

SPECIMEN LABEL

TRANSMISSION & ALUMINUM CLEANER is a balanced blend of concentrated, completely soluble powders specially combined to function most efficiently at elevated temperatures. These powerful cleaners strip away oil, grease, and other deposits from transmissions, radiators, and other metal parts.

DIRECTIONS

For Use In Spray Cabinets: Use 1 to 2 ounces of TRANSMISSION & ALUMINUM CLEANER per gallon of tank water. Spray cabinet temperature should be run and maintained at 190°F. The pH level of the spray cabinet solution should be maintained at 12 to 13. If foaming becomes a problem in the spray cabinet it is usually due to the surfactants in the greases and oils that are being removed from the parts. If this happens, be sure to use the spray cabinet oil skimmer, or clean out the spray cabinet of any oily residue. Share's FOAM MASTER may also be used to control foaming problems. When disposing of the water in the spray cabinet be sure to adjust the pH back down close to neutral (7) with Share's ACID pH ADJUSTMENT. The sludge at the bottom of the spray cabinet must be disposed of in a proper fashion, most likely with waste oil.

For Use As A Dipping Solution: Dissolve 1 ounce of TRANSMISSION & ALUMINUM CLEANER per gallon of water in dipping tank. Maintain water temperature at or above 190°F. Dip parts to be cleaned into the solution, let soak for 15 to 20 minutes, then rinse. More TRANSMISSION & ALUMINUM CLEANER may be added for extremely soiled parts.

WARNING

HARMFUL IF SWALLOWED.

Eye irritant. Avoid contact with eyes. Do not mix with any other chemical.

FIRST AID:

IF SWALLOWED: DO NOT induce vomiting. Contact physician or poison control center immediately.

IF IN EYES: Flush eyes and under eyelids with cool water for at least 15 minutes.

IF ON SKIN: Wash skin with soap and water. Remove all contaminated clothing and launder separately before reuse.

If irritation persists, contact a physician.

IF INHALED: Remove person to fresh air. If irritation persists, contact a physician.

KEEP OUT OF REACH OF CHILDREN

This product contains	CAS Number
Sodium Carbonate	.497-19-8
Sodium Sulfate	.7757-82-6
Sodium Metasilicate	.6348-92-0
Sodium Tripolyphosphate	.7758-29-4
Sodium Dichloroisocyanurate	.51580-86-0

0664 • 042009

NFPA RATINGS
Flammability

