



TRIDENT

WATER TREATMENT

TRIDENT

WATER TREATMENT

BOILERPRO H

BOILERPRO H

STEAM BOILER WATER TREATMENT
PROVIDES SUPERIOR PROTECTION IN HARD WATER SYSTEMS
PREVENTS LIME, SCALE, RUST AND MINERAL DEPOSITS

DANGER

Causes severe skin burns and eye damage.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 5 20 35 55 Gallon(s)



P.O. Box 245013
Milwaukee, WI 53224
(800) 776-7192
www.sharecorp.com



Do not breathe mist, spray. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

Store locked up.

Dispose of contents/container to comply with local/regional/national/international regulations.

For industrial and commercial use only.
For additional information, see Safety Data Sheet.

NFPA* RATINGS:
Health: 2; Flammability: 0; Reactivity: 0

CONTAINS/CAS#:
Water/7732-18-5; Proprietary/Mixture;
Potassium Carbonate/584-08-7; Sodium Hydroxide/1310-73-2; Sodium Lignosulfonate/8061-51-6

0903.050615



Please Recycle.

BOILERPRO H is a phosphate free, carbonate-based formulation that works extremely well at high calcium and magnesium ion concentrations. It combines an alkalinity builder with hardness control, plus a polymeric sludge dispersant to remove and control scale and sludge deposits.

DIRECTIONS:

The dosage of **BOILERPRO H** will depend on the percent of condensate returned, makeup water characteristics and initial cleanliness of heat transfer surfaces. The treatment program must be accompanied by a program of regular blowdown to remove sludge and suspended solids from the boiler.

BOILERPRO H may be fed on a "one shot" basis or with an automated continuous system. Gradual and continuous feeding is recommended for industrial process and other large boilers. It is recommended the **BOILERPRO H** be mixed with other boiler treatment chemicals, especially a steam line treatment and oxygen scavengers where needed, and diluted with water for convenient feeding. If the boiler water system has not been previously treated, add a starting dosage of twice the recommended amount for weekly dosages for the first four weeks.

For weekly maintenance: Add 1/2 gallon (2 quarts) of BOILERPRO H per week for each 25 horsepower versus the boiler's operational horsepower. Control the level of BOILERPRO H by maintaining a phenol(P) alkalinity level of between 500-700ppm.

Blowdown: Open the blowdown valve until the level drop in the sight glass is reached, recommended starting point is 2 inches twice a week. Blowdown schedules will vary depending upon water hardness and cycles of concentration.

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com

SPECIMEN LABEL