



# TRIDENT

WATER TREATMENT

## BOILERPRO OXY PLUS

**LIQUID OXYGEN SCAVENGER**

MINIMIZES OXYGEN PITTING

WORKS IN SYSTEMS WITH OR WITHOUT A DEAERATING HEATER

**DANGER**

*Causes serious eye damage.*

**KEEP OUT OF REACH OF CHILDREN**

NET CONTENTS:  1  5  20  35  55 Gallon(s)

# TRIDENT

WATER TREATMENT

## BOILERPRO OXY PLUS



**P.O. Box 245013  
Milwaukee, WI 53224  
(800) 776-7192**

[www.sharecorp.com](http://www.sharecorp.com)



## BOILERPRO OXY PLUS



**DANGER:** Causes serious eye damage.

*Wear eye protection, protective clothing, protective gloves.*

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

*Offer empty container for recycling. If recycling is not available, discard container in trash.*

*For industrial and commercial use only. For additional information, see Safety Data Sheet.*

**NFPA® RATINGS:**

*Health: 2; Flammability: 0; Reactivity: 0*

**CONTAINS/CAS#:**

*Water (7732-18-5); Sodium Metabisulfite (7681-57-4); Sodium Sulfite (7757-83-7); Sodium Sulfate (7757-82-6); Cobalt monosulfate heptahydrate (10026-24-1).*

**⚠ WARNING:** This product can expose you to Cobalt sulphate, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

0927.111221

**BOILERPRO H** is a phosphate free, carbonate-based formulation that works extremely well at high calcium and magnesium ion concentrations. It combines an alkalinity builder with hardness control, plus a polymeric sludge dispersant to remove and control scale and sludge deposits.

**DIRECTIONS:**

*The dosage of BOILERPRO H will depend on the percent of condensate returned, makeup water characteristics and initial cleanliness of heat transfer surfaces. The treatment program must be accompanied by a program of regular blowdown to remove sludge and suspended solids from the boiler.*

**BOILERPRO H** may be fed on a "one shot" basis or with an automated continuous system. Gradual and continuous feeding is recommended for industrial process and other large boilers. It is recommended the **BOILERPRO H** be mixed with other boiler treatment chemicals, especially a steam line treatment and oxygen scavengers where needed, and diluted with water for convenient feeding. If the boiler water system has not been previously treated, add a starting dosage of twice the recommended amount for weekly dosages for the first four weeks.

**For weekly maintenance:** Add 1/2 gallon (2 quarts) of BOILERPRO H per week for each 25 horsepower versus the boiler's operational horsepower. Control the level of BOILERPRO H by maintaining a phenol(P) alkalinity level of between 500-700ppm.

**Blowdown:** Open the blowdown valve until the level drop in the sight glass is reached, recommended starting point is 2 inches twice a week. Blowdown schedules will vary depending upon water hardness and cycles of concentration.



Please Recycle.

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • [www.sharecorp.com](http://www.sharecorp.com)