

OIL AND GREASE ELIMINATOR

Oil and Grease Emulsifier

Form: Liquid

Color: Colorless

Odor: Slight Detergent

pH: 7.0-8.0

Solubility (in water): Soluble
(in mineral spirits): Insoluble

VOC Content (% by wt): N/D

Flash Point (ASTM D-7821): N/A

Specific Gravity: 1.01 g/cm³

Density: 8.43 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

| | <u>C.A.S. #</u> |
|--------------------------------------|-----------------|
| Water | 7732-18-5 |
| Poly (oxyethylene) Nonylphenol | 5016-45-9 |
| Sodium Xylene Sulfonate | 1300-72-7 |
| Ethoxylated Octyl Phenol | 9036-19-5 |
| Diazolidinyl Urea..... | 491-02-8 |

| Emulsifies: |
|---|
| <ul style="list-style-type: none"> • Grease • Fuel Oil • Gasoline • Solvents • Hydrocarbons • Diesel Fuel • Oil |
| For use by... |
| <ul style="list-style-type: none"> • Fire Departments • Sewage Treatment Plants • Port Authorities • Waste Management Sites • Municipalities |

DIRECTIONS: For gasoline, solvent or fuel spills, apply OIL AND GREASE ELIMINATOR at full strength or diluted 1:1 with water. Allow to penetrate spill and hose off with water under pressure. For oil slicks, apply a sufficient quantity of OIL AND GREASE ELIMINATOR so as to "break up" the slick. Agitate mechanically, if possible, in order to mix the oil with the water base.

FOR MORE DETAILED INSTRUCTIONS PLEASE CONSULT
PRODUCT LABEL.

| HMIS | | NFPA |
|--------------------------|----------------------------|------------------------------|
| | Severe 4 Extreme | |
| Health | Serious 3 High | Health..... 0 |
| Flammability..... | Moderate 2 Moderate | Flammability..... 0 |
| Reactivity..... | Slight 1 Slight | Reactivity..... 0 |
| Personal Protection..... | Minimal 0 Insignificant | Special Precautions.....None |