

THERMO THAW

Environmentally Safe Ice Melter

Form: Granules

Color: White

Odor: None

pH: N/A

Solubility (in water): Soluble
(in mineral spirits): Insoluble

VOC Content (% by weight): N/D

Flash Point (ASTM D-7821): Non-combustible

Density: 40.0 – 70.0 lbs/ft³

Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Magnesium Chloride.....	7786-30-3
Sodium Chloride.....	7647-14-5
Calcium Chloride.....	10043-52-4

Use on...
• Sidewalks
• Driveways
• Steps
• Streets
• Loading Docks
• Porches
• Ramps
• Drain Pipes

DIRECTIONS: Spread at a rate of about 1/4 cup per square yard. Leaves no messy white residue to coat sidewalks or to be tracked into buildings. Remove slush immediately to prevent penetration of porous areas and cracks in the concrete, as continual thawing and freezing action can cause damage to poor quality concrete. Will not harm carpet or flooring.

PRECAUTION: Do not use on concrete less than 1 year old. THERMO THAW should not be used on pre-cast masonry walks or steps, or on any questionable quality concrete or used in excessive amounts. Excessive amounts may cause surface flaking or scaling and increase the freeze/thaw cycle increasing the chance of chipping and cracking.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	0
Flammability.....	Moderate	2	Moderate	Flammability.....	0
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None