

# CAPTURE

## Absorbent

**Form:** Powder

**Color:** White

**Odor:** Essentially odorless

**pH:** N/A

**Solubility (in water):** Slight  
**(in mineral spirits):** N/D

**Viscosity (CPS at 70°F):** N/A

**Flash Point (ASTM D-7821):** N/A

**Specific Gravity:** 0.91 g/cm<sup>3</sup>

**Density:** 7.59 lbs/gal

**Storage Stability (at 70°F):** 1 year

**Ingredients**

Block Copolymer ..... **C.A.S. #** Proprietary

### Picks up...

- **Petroleum Hydrocarbons**
- **Fuels**
- **Solvents**
- **Motor Oils & Crude Oil**
- **Gasoline & Diesel Fuel**
- **Transmission & Brake Fluid**
- **Hydraulic Fluid**

**DIRECTIONS:** Distribute CAPTURE granules evenly over the spilled hydrocarbons, encapsulation will begin immediately. Let CAPTURE work for 5 – 15 minutes after application. Thin liquids absorb faster than viscous oils.

For oil floating on water, apply CAPTURE liberally, allow time to absorb and contain, remove with a screen. Typical disposal methods are sanitary landfill or incineration of the waste, consistent with local and applicable regulations. Always check your local regulations.

HMIS®			NFPA		
Health.....	1	Severe 4	Extreme	Health.....	1
Flammability.....	1	Serious 3	High	Flammability.....	1
Reactivity.....	0	Moderate 2	Moderate	Reactivity.....	0
Personal Protection.....	None	Slight 1	Slight	Special Precautions.....	None
		Minimal 0	Insignificant		