

LIQUI-GEM SAPPHIRE

Crosslinked Acrylic Floor Finish

Form: Liquid

Color: Opaque White

Odor: Mild

pH: 8.0 - 8.75

Polymer Type: Zinc Crosslinked Acrylic

Solids Content: 22%

Solubility (in water): Soluble
(in mineral spirits): Insoluble

Flash Point (ASTM D-7821): None

Specific Gravity: 0.97 g/cm³ ± 0.05

Density: 8.09 ± 0.05 lbs /gal

Storage Stability (at 70°F): Minimum 1 year
(at 0°F): Damaged by Freezing

Ingredients

C.A.S.

Water.....	7732-18-5
Diethylene Glycol Methyl Ether.....	111-77-3
Zinc Ammonium Carbonate.....	38714-47-5
Dibutyl Phthalate	84-74-2
Tributoxyethyl Phosphate	78-51-3

Other Uses...

- **Terrazzo Finish**
- **Desk Top Sealer**
- **Wood Floor Sealer**
- **Wood Wall Sealer**
- **Mold Release Agent**
- **Concrete Floor Finish**
- **Quarry Tile Polish**
- **Marble Polish**

APPLICATION: Remove old wax or finish using either LIQUI-GEM MARQUISE CUT or LIQUI-GEM PRINCESS CUT. Rinse floor several times with clean water. Then use LIQUI-GEM BALANCE to neutralize excess alkalinity, rinse floor with water and allow floor to dry thoroughly. Apply smooth even coats of LIQUI-GEM SAPPHIRE using a previously rinsed cotton string mop or lambswool applicator. Allow 30 minutes for drying before applying the next coat of LIQUI-GEM SAPPHIRE.

HMIS			NFPA		
Health	1	Severe 4	Extreme	Health	1
Flammability.....	0	Serious 3	High	Flammability	0
Reactivity.....	0	Moderate 2	Moderate	Reactivity	0
Personal Protection.....	X	Slight 1	Slight	Special Precautions.....	None
		Minimal 0	Insignificant		

KEEP FROM FREEZING

Share Corporation • P.O. Box 245013 • Milwaukee, WI 53224 • 800-776-7192