



Liqui-Gem

EMERALD

16% SOLIDS ACRYLIC FLOOR FINISH

CROSSLINKED POLYMERS

HIGH GLOSS AND SUPERIOR WEAR RESISTANCE

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: ■ 1 ■ 5 ■ 20 ■ 35 ■ 55 Gallon(s)

Liqui-Gem EMERALD



PO BOX 245013
MILWAUKEE, WI 53224
800.776.7192
www.sharecorp.com



Liqui-Gem

EMERALD

DISPOSAL: Offer empty container for recycling. If recycling is not available, discard container in trash.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

NFPA® RATINGS:

Health: 0; Flammability: 1; Reactivity: 0

INGREDIENTS/CAS #:

Acrylic Polymer/Proprietary; Water/7732-18-5;
Diethylene Glycol Monoethyl Ether/111-90-0;
Tributoxyethyl Phosphate/78-51-3; Zinc
Oxide/1314-13-2

APPLICATION DIRECTIONS:

- Remove old wax or finishes using **LIQUI-GEM MARQUISE CUT**.
- Neutralize stripper residue utilizing **LIQUI-GEM BALANCE**.
- Rinse floor with water and allow to dry.
- Seal floor surface with 2 coats of **LIQUI-GEM SETTING**.
- Apply a smooth, even coat of **LIQUI-GEM EMERALD** using a previously rinsed cotton string mop or lamb's wool applicator.
- Allow 30 minutes for drying between coats of **LIQUI-GEM EMERALD**.
- For floors subject to frequent burnishing operations, apply 2 to 4 coats of **LIQUI-GEM EMERALD**.

MAINTENANCE DIRECTIONS:

- Daily damp mopping removes dirt that may scratch or abrade finish. Utilize **LIQUI-GEM WASH** for all your damp mopping needs.
- After damp mopping, **LIQUI-GEM EMERALD** can be repaired and maintained using conventional spray buffing techniques.
- Use **LIQUI-GEM REVITALIZE** to restore the finish to an incredible shine.

KEEP FROM FREEZING.



Please Recycle.

1704.051115