

SUPER IMPACT GREASE

Heavy Duty Shock Resistant Grease

Form: Semi-Solid

Color: Green or blue

Odor: Slight Petroleum

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

Flash Point (°F): 455

Specific Gravity: 0.96 g/cm³

Density: 8.01 lbs/gal

Storage Stability (at 70°F): 1 year

Great for use in...

- **Paper Machine Wet Ends**
- **Winter DOT Equipment**
- **Steel Foundries**
- **Marine Equipment**
- **Oil Fields**
- **Elevators**
- **Boiler Operations**
- **Mining Equipment**
- **Sewage Plants**
- **Farm Equipment**
- **Air Conditioners**
- **Wheel Bearings**

TYPICAL SPECIFICATIONS

NLGI Grade	2
Color	Green or Blue
Thickener Type	Calcium Sulfonate Complex
Viscosity @ 40°C, cSt	220
Viscosity Index	97
Penetration Worked	265-295
Dropping Point (°F).....	+550
Timken OK Load (lbs)	65
Weld Load, kg, ASTM D 2596.....	620
Load Wear Index.....	65
Wheel Bearing Leakage	5.0 MAX
Water Washout @ 175°F, % wt.....	3.0

HMIS®				NFPA	
		Severe	4	Extreme	
Health	1	Serious	3	High	Health..... 1
Flammability	1	Moderate	2	Moderate	Flammability..... 1
Physical Hazard	0	Slight	1	Slight	Reactivity..... 0
Personal Protection.....	X	Minimal	0	Insignificant	Special Precautions.....None