

# PAN PUCKS

For Condensate Drain Pans



**Form:** Solid Block

**Color:** Yellow, Blue, Red

**Odor:** Fresh

**pH:** 8.3 (10% solution)

**Solubility (in water):** Soluble  
**(in mineral spirits):** No data available

**VOC Content (% by weight):** N/D

**Flash Point (ASTM D-7821):** N/A

**Specific Gravity:** 0.98 g/cm<sup>3</sup>

**Density:** 8.19 lbs/gal

**Storage Stability (at 70°F):** 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Urea .....	57-13-6
Benzyl-C12-18-alkyldimethyl ammonium chlorides .....	68391-01-5

Use In...
• <b>Fan Coil Air Conditioner</b>
• <b>Ceiling Air Conditioning Units</b>
• <b>Roof Mounted Units</b>
• <b>Refrigerated Vending Machines</b>
• <b>Beverage Coolers</b>
• <b>Grocery Reach-In Coolers</b>
• <b>Cold Storage Walk-Ins</b>

**DIRECTIONS:** The PAN PUCK is simple to install. Place the unit under the cooling coil in the middle of the pan length. Unit must be in contact with the condensate in the pan. PAN PUCK locks itself into place and will dissolve completely.

PAN PUCK – PeeWee (yellow): Treats up to 5 tons.

PAN PUCK – Jr. (blue): Treats up to 7.5 tons.

PAN PUCK – Pro (red): Treats up to 15 tons.

**NOTE:** Each puck lasts 6 months based on an average 8-hour air-conditioning day.

HMIS®			NFPA®		
	Severe	4	Extreme		
Health .....	Serious	3	High	Health .....	2
Flammability.....	Moderate	2	Moderate	Flammability.....	0
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None