



# TRIDENT

WATER TREATMENT

## CYCLO-PLUS

### CLOSED LOOP SYSTEM TREATMENT

MOLYBDATE SCALE AND CORROSION INHIBITOR  
FOR USE IN BOTH HOT OR COLD WATER CLOSED LOOP SYSTEMS

#### DANGER

May be corrosive to metals.  
Causes severe skin burns and eye damage.

**KEEP OUT OF REACH OF CHILDREN**

NET CONTENTS:  1  5  20  35  55 Gallon(s)

# TRIDENT

WATER TREATMENT

## CYCLO-PLUS



**P.O. Box 245013**  
**Milwaukee, WI 53224**  
**(800) 776-7192**  
**www.sharecorp.com**



#### DANGER:

May be corrosive to metals. Causes severe skin burns and eye damage.

#### PREVENTION:

Keep only in original container. Do not breathe spray, mist. Wash thoroughly after handling. Wear eye protection, protective gloves, protective clothing. Wash contaminated clothing before reuse.

**IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting.

**IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water/shower.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner.

**DISPOSAL:** Dispose of contents/container to comply with local/regional/national/international regulations.

*For industrial and commercial use only.*

*For additional information, see Safety Data Sheet.*

**WARNING:** This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.



Please Recycle.

**TRIDENT CYCLO-PLUS** from Share is a molybdate-based closed loop system treatment that effectively rids your system of scale as it provides a layer of protection against corrosion. Specifically formulated for closed loop units, this convenient liquid is engineered for use in all heat exchange situations.

#### DIRECTIONS:

The dosage of **TRIDENT CYCLO-PLUS** will depend on the amount of water contained in the recirculating system. Normal treatment dosage is 1 gallon of **TRIDENT CYCLO-PLUS** for every 125 gallons of water contained in the system. **TRIDENT CYCLO-PLUS** may be injected directly into the recirculating system through the use of a regular bypass feeder. Mild steel piping and feeding equipment may be used. Control the level of **TRIDENT CYCLO-PLUS** by maintaining a phosphate (PO4) level of between 3.0 - 5.0 ppm.

In chilled water recirculating systems, a microbiocide is recommended as a preventative treatment or for control if infestation occurs. Many hot water and chilled water recirculating systems may require the use of an oxygen scavenger, like **TRIDENT BOILERPRO OXY PLUS**. Control **TRIDENT BOILERPRO OXY PLUS** feed rates by maintaining a sulfite (SO3) level of between 20 - 40 ppm.

**WARNING:** This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

#### NFPA\* RATINGS:

Health: 2; Flammability: 0; Reactivity: 0

#### CONTAINS/CAS#:

Water (7732-18-5); Corrosion and Scale Inhibitor (Mixture); Potassium Hydroxide (1310-58-3); Acrylamide Copolymer (Proprietary); Benzotriazole (95-14-7)