



# Acrylic Clear

## FLEXIBLE CLEAR COATING

- Seals out dirt, oil and harmful chemicals

- UV ray resistant

- Rust inhibitor

Net Weight: 12 Oz. (340g)

### DANGER!

EXTREMELY FLAMMABLE LIQUID AND VAPOR.  
VAPORS MAY CAUSE FLASH FIRE.  
CONTENTS UNDER PRESSURE. VAPOR HARMFUL.  
See other cautions on back side panel.

**KEEP OUT OF REACH OF CHILDREN**



### DANGER

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

### PREVENTION

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use. Obtain special instructions before use. Keep away from heat, sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Do not breathe dust/fume/gas/mist/vapors/spray.

### RESPONSE

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a poison center/doctor if you feel unwell.

**IF SKIN IRRITATION OCCURS:** Get medical advice/attention.

**IF ON SKIN:** Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

### STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place. Keep container tightly closed.

### DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.



**ACRYLIC CLEAR** is a durable, flexible acrylic coating for wood, metal, and masonry surfaces. It is an ideal moisture barrier, prevents arcing, and protects against oil, dirt, salt and acids. Protects vehicle ignition systems, preserves battery terminals from corrosion and also prevents tarnish on decorative brass and copper.

### DIRECTIONS

Surface must be free of dirt, moisture, grease, loose rust and paint. Shake can vigorously for one minute after agitator begins to rattle, and shake often during use. Hold nozzle 10 to 12 inches from surface and apply by spraying in quick, short bursts. Apply several thin coats rather than a single heavy coat. For best results, use when temperature is above 65°F and humidity below 85 percent. After use, clear the nozzle by turning can upside down and pressing valve for 1 to 2 seconds.

### INGREDIENTS/CAS #

Acetone (67-64-1)  
Propane (74-98-6)  
Toluene (108-88-3)  
n-butane (106-97-8)  
VM&P Naphtha (64742-89-8)  
Glycol Ether EB (111-76-2)  
Xylene (mix) (1330-20-7)

### WARNING

This product can expose you to toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### NFPA® Ratings

Health: 2; Flammability: 4; Reactivity: 0



Please Recycle.

8001.012618

Sold by: