



# Rubber In a Can KLEAR

**SEALS OUT MOISTURE**

**PAINTABLE**

**PREVENTS RUST FORMATION**

**CONTAINS NO OZONE  
DEPLETING CHEMICALS**

**FOR INDUSTRIAL/PROFESSIONAL USE ONLY NOT FOR RETAIL SALE.**

**See back panel for further precautions and first aid instructions.**

**NET WEIGHT: 15 ounces (425 grams)**

**RUBBER IN A CAN KLEAR provides superior protection for fender replacements, section repairs and weld joints. It also depresses sound, retards salt corrosion, and seals water leaks. RUBBER IN A CAN KLEAR may be used on concrete and asphalt driveways, gutters and flashings and roofs.**



**DANGER:**

EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. HARMFUL IF INHALED OR IN CONTACT WITH SKIN. CAUSES SKIN AND SERIOUS EYE IRRITATION. SUSPECTED OF CAUSING CANCER. MAY CAUSE RESPIRATORY IRRITATION, DROWSINESS OR DIZZINESS. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

**PREVENTION:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash hands and face thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Intentional misuse by deliberately concentrating and inhaling the vapor of the contents may be harmful or fatal.

**RESPONSE:**

If exposed or concerned: Get medical advice/attention.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**IF ON SKIN:** Gently wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

**IF SWALLOWED:** Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

**STORAGE:**

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**DISPOSAL:**

Dispose of contents/container to an approved waste disposal plant.

**INGREDIENTS/CAS#:** Methyl Acetate (79-20-9), Propane/Isobutane/N-Butane (68476-86-8), Petroleum Distillates (64742-89-8), Xylene (1330-20-7), Acetone (67-64-1), Synthetic Amorphous Silica (112926-00-8), Ethyl benzene (100-41-4), bis (2-ethylhexyl) terephthalate (6422-86-2), Polystyrene (9003-53-6), Methanol (67-56-1).

**DIRECTIONS: SHAKE WELL BEFORE USING.** Make sure surface is clean, dry and free of dirt and rust. Hold can 12 inches from surface. Spray a thin even coat building up to the desired thickness. Remove overspray with a cloth dampened with kerosene.

**Coverage:** 10 to 20 square feet per can.

**Temperature:** Both surface and at use temperature should be between -10°F to 150°F.

**WARNING!**

This product contains chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

**KEEP OUT OF REACH OF CHILDREN**

Refer to SDS for further information

**SOLD BY:**

**8003 • 050415**