

Silicone RTV-White

Safety Data Sheet



SECTION 1: Product and company identification

Product name : Silicone RTV-White
Use of the substance/mixture : Aerosol
Adhesive
Product code : 805201
Company : Share Corporation
P.O. Box 245013
Milwaukee, WI 53224 - USA
T (414) 355-4000
Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Compressed gas H280
Skin Irrit. 2 H315
Eye Irrit. 2A H319

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : Contains gas under pressure; may explode if heated
Causes skin irritation
Causes serious eye irritation

Precautionary statements (GHS-US) : Wash thoroughly after handling
Wear protective gloves, face protection, eye protection
If on skin: Wash with plenty of soap and water
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Specific treatment (see First aid measures on this label)
If skin irritation occurs: Get medical advice/attention
If eye irritation persists: Get medical advice/attention
Take off contaminated clothing and wash it before reuse
Protect from sunlight. Store in a well-ventilated place

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

| Name | Product identifier | % | Classification (GHS-US) |
|---|---------------------|-------|---------------------------|
| triacetoxyethylsilane | (CAS No) 17689-77-9 | 1 - 5 | Acute Tox. 4 (Oral), H302 |
| methyltriacetoxyethylsilane | (CAS No) 4253-34-3 | 1 - 5 | Not classified |
| 1,1-difluoroethane, liquefied, under pressure | (CAS No) 75-37-6 | 1 - 5 | Not classified |

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Silicone RTV-White

Safety Data Sheet



- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Artificial respiration and/or oxygen if necessary. Call a poison center or a doctor if you feel unwell. If unconscious, place in the recovery position and seek medical advice. Loosen tight clothing such as a collar, tie, belt or waistband.
- First-aid measures after skin contact : Rinse skin with water/shower. Consult a doctor/medical service. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth with water. Drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Causes serious eye irritation. Causes skin irritation. Irritation to throat.
- Symptoms/injuries after inhalation : Decomposition products may be a hazard to health. The effects may be delayed.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : Irritating to mouth, throat and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Symptoms may be delayed. Keep watching the victim.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Adapt extinguishing media to the environment.

5.2. Special hazards arising from the substance or mixture

- Explosion hazard : Contains gas under pressure; may explode if heated.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate unnecessary personnel. Gas is denser than air. May accumulate in low areas e.g. close to the ground. Stay upwind/keep distance from source.

6.1.1. For non-emergency personnel

- Protective equipment : Do not enter without an appropriate protective equipment.
- Emergency procedures : Only qualified personnel equipped with suitable protective equipment may intervene. Evacuate unnecessary personnel. DO NOT touch spilled material.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment.
- Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Avoid discharge to the environment. Advise local authorities if considered necessary.

6.3. Methods and material for containment and cleaning up

- For containment : Move the cylinder to a safe and open area if the leak is irreparable. Prevent the product from entering drains or confined areas. For further information refer to section 8 : Exposure-controls/personal protection".
- Methods for cleaning up : Clean contaminated surfaces with an excess of water. Carefully collect the spill/leftovers.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Do not re-use empty containers. Keep container tightly closed. Use personal protective equipment as required. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work.
- Hygiene measures : Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Do not puncture, incinerate or crush.

Silicone RTV-White

Safety Data Sheet



- Storage conditions : Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep only in the original container in a cool, well ventilated place away from : Incompatible substances or mixtures, Keep away from food and drink. Keep container tightly closed.
- Incompatible materials : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.
- Storage area : Keep out of direct sunlight. Store in a cool area. Store in a dry area. Store in a well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Personal protective equipment : Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Safety glasses. Protective clothing.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Gas
- Appearance : Aerosol. White. Paste.
- Odor : Vinegar odour
- Odor threshold : No data available
- pH : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : > 212 °F Closed cup
- Relative evaporation rate (butyl acetate=1) : No data available
- Flammability (solid, gas) : No data available
- Explosion limits : No data available
- Explosive properties : No data available
- Oxidizing properties : No data available
- Vapor pressure : No data available
- Relative density : No data available
- Relative vapor density at 20 °C : No data available
- Specific gravity / density : 1.007 g/ml
- Solubility : No data available
- Log Pow : No data available
- Log Kow : No data available
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Viscosity : No data available
- Viscosity, kinematic : No data available
- Viscosity, dynamic : No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur. No dangerous reactions known under normal conditions of use.

Silicone RTV-White

Safety Data Sheet



10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| | |
|--|---|
| triacetoxylethylsilane (17689-77-9) | |
| LD50 oral rat | 1460 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Experimental value) |
| methyltriacetoxysilane (4253-34-3) | |
| LD50 oral rat | 2060 mg/kg (Rat; Literature) |
| 1,1-difluoroethane, liquefied, under pressure (75-37-6) | |
| LC50 inhalation rat (mg/l) | 176 mg/l/4h (Rat; Literature study) |
| LC50 inhalation rat (ppm) | 64000 ppm/4h (Rat; Literature study) |

| | |
|--|---|
| Skin corrosion/irritation | : Causes skin irritation. |
| Serious eye damage/irritation | : Causes serious eye irritation. |
| Respiratory or skin sensitization | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| Specific target organ toxicity (single exposure) | : Not classified |
| Specific target organ toxicity (repeated exposure) | : Not classified. |
| Aspiration hazard | : Not classified |
| Symptoms/injuries after inhalation | : Decomposition products may be a hazard to health. The effects may be delayed. |
| Symptoms/injuries after skin contact | : Causes skin irritation. |
| Symptoms/injuries after eye contact | : Causes serious eye irritation. |
| Symptoms/injuries after ingestion | : Irritating to mouth, throat and stomach. |
| Likely routes of exposure | : Skin and eyes contact.;Inhalation;Ingestion. |

SECTION 12: Ecological information

12.1. Toxicity

| | |
|--|---|
| triacetoxylethylsilane (17689-77-9) | |
| LC50 fish 1 | 251 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value) |
| EC50 Daphnia 1 | 62 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value) |
| EC50 Daphnia 2 | 43 mg/l (NOEC; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value) |
| Threshold limit algae 1 | 76 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value) |
| Threshold limit algae 2 | 73 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value) |

12.2. Persistence and degradability

| | |
|--|---|
| triacetoxylethylsilane (17689-77-9) | |
| Persistence and degradability | Readily biodegradable in water. Hydrolysis in water. Highly mobile in soil. |
| methyltriacetoxysilane (4253-34-3) | |
| Persistence and degradability | Biodegradability in water: no data available. |
| 1,1-difluoroethane, liquefied, under pressure (75-37-6) | |
| Persistence and degradability | Biodegradability in water: no data available. |

Silicone RTV-White

Safety Data Sheet



12.3. Bioaccumulative potential

| | |
|---|--|
| triacetoxylethylsilane (17689-77-9) | |
| Log Pow | -1.9 (QSAR; KOWWIN; 20 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |
| methyltriacetoxysilane (4253-34-3) | |
| Log Pow | 0.25 (Estimated value) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |
| 1,1-difluoroethane, liquefied, under pressure (75-37-6) | |
| Log Pow | 0.75 (Experimental value) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--------------------------------|--|
| Waste treatment methods | : Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container to comply with local/regional/national/international regulations. |
| Waste disposal recommendations | : Container under pressure. Do not drill or burn even after use. Dispose of contents/container to comply with local/regional/national regulations. Do not discharge into drains or the environment. Do not discharge into the sewer. |

SECTION 14: Transport information

Department of Transportation (DOT)

| | |
|----------------------------------|---|
| Transport document description | : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1 |
| UN-No.(DOT) | : UN1950 |
| Proper Shipping Name (DOT) | : Aerosols flammable, (each not exceeding 1 L capacity) |
| Transport hazard class(es) (DOT) | : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115 |
| Hazard labels (DOT) | : 2.1 - Flammable gas |



| | |
|--|--|
| DOT Packaging Non Bulk (49 CFR 173.xxx) | : None |
| DOT Packaging Bulk (49 CFR 173.xxx) | : None |
| DOT Special Provisions (49 CFR 172.102) | : N82 |
| DOT Packaging Exceptions (49 CFR 173.xxx) | : 306 |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 75 kg |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) | : 150 kg |
| DOT Vessel Stowage Location | : A |
| DOT Vessel Stowage Other | : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials |

Additional information

| | |
|-------------------|---|
| Other information | : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.306. |
|-------------------|---|

ADR

No additional information available

Transport by sea

| | |
|-----------------------------|-------------------------|
| UN-No. (IMDG) | : UN1950 |
| Proper Shipping Name (IMDG) | : Aerosols, flammable |
| Class (IMDG) | : 2.1 - Flammable gases |

Air transport

| | |
|-----------------------------|---------------------------|
| UN-No.(IATA) | : UN1950 |
| Proper Shipping Name (IATA) | : Aerosols, flammable |
| Class (IATA) | : 2.1 - Gases : Flammable |

Silicone RTV-White

Safety Data Sheet



SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

California Proposition 65 - This product does not contain a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

| | |
|---------------------|--|
| Acute Tox. 4 (Oral) | Acute toxicity (oral) Category 4 |
| Compressed gas | Gases under pressure Compressed gas |
| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| H280 | Contains gas under pressure; may explode if heated |
| H302 | Harmful if swallowed |
| H315 | Causes skin irritation |
| H319 | Causes serious eye irritation |

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.