

# Four Way Action N.C.

## Safety Data Sheet



### SECTION 1: Product and company identification

Product name : Four Way Action N.C.  
Use of the substance/mixture : Lubricant.  
Aerosol  
Product code : 809501  
Company : Share Corporation  
P.O. Box 245013  
Milwaukee, WI 53224 - USA  
T (414) 355-4000  
Emergency number : Chemtrec: (800) 424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Aerosol 1 H222  
Asp. Tox. 1 H304  
Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger  
Hazard statements (GHS-US) : Extremely flammable aerosol  
May be fatal if swallowed and enters airways  
Precautionary statements (GHS-US) : Keep away from heat, sparks, open flames, hot surfaces. - No smoking  
Do not spray on an open flame or other ignition source  
Pressurized container: Do not pierce or burn, even after use  
If swallowed: Immediately call a doctor, a POISON CENTER  
Do NOT induce vomiting  
Store locked up  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
Dispose of contents/container to comply with local/regional/national/international regulations

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

### SECTION 3: Composition/information on ingredients

#### 3.1. Substance

Not applicable

Full text of H-phrases: see section 16

#### 3.2. Mixture

| Name  | Product identifier  | %        | Classification (GHS-US)                   |
|---|---------------------|----------|---|
| hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics | (CAS No) 64742-47-8 | 40 - 60  | Flam. Liq. 4, H227<br>Asp. Tox. 1, H304   |
| Distillates (petroleum), solvent-dewaxed heavy paraffinic             | (CAS No) 64742-65-0 | 10 - 20  | Carc. 1B, H350<br>Asp. Tox. 1, H304       |
| 2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether          | (CAS No) 112-34-5   | 2.5 - 10 | Eye Irrit. 2A, H319                       |
| propane   | (CAS No) 74-98-6    | 2.5 - 10 | Flam. Gas 1, H220<br>Compressed gas, H280 |

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general : Take off immediately all contaminated clothing. If you feel unwell, seek medical advice. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. show this sheet where possible. Wash contaminated clothing before reuse.  
First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

# Four Way Action N.C.

## Safety Data Sheet



- First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse with water. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a physician immediately. Rinse mouth. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : Contact during a long period may cause light irritation.
- Symptoms/injuries after eye contact : Direct contact with the eyes is likely irritating.
- Symptoms/injuries after ingestion : Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. Risk of lung edema.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Powder. Alcohol-resistant foam. Water fog. Carbon dioxide.
- Unsuitable extinguishing media : Do not use a water jet since it may cause the fire to spread.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol.
- Explosion hazard : Contains gas under pressure; may explode if heated.
- Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

### 5.3. Advice for firefighters

- Firefighting instructions : In case of fire and/or explosion do not breathe fumes. Move containers away from the fire area if this can be done without risk. NEVER direct water jet on liquid. Use water spray or fog for cooling exposed containers. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Some of these materials, if spilled, may evaporate leaving a flammable residue.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate unnecessary personnel. Stay upwind/keep distance from source. Gas is denser than air. May accumulate in low areas e.g. close to the ground. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Do not enter without an appropriate protective equipment. Do not breathe gas/vapor. DO NOT touch spilled material. Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire.
- Emergency procedures : Ventilate the area thoroughly, especially low lying areas (basements, work pits etc.). Advise local authorities if considered necessary.

#### 6.1.2. For emergency responders

No additional information available

### 6.2. Environmental precautions

Avoid discharge to the environment. Do not contaminate water with the product or its container. Do not allow to enter drains or water courses.

### 6.3. Methods and material for containment and cleaning up

- For containment : Eliminate every possible source of ignition. NO open flames, NO sparks, and NO smoking. Keep combustibles (wood, paper, oil, etc.) away from spilled material. Form with air vapors (heavier than air) who stay on the floor. Gas is denser than air. May accumulate in low areas e.g. close to the ground. This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways. Stop leak if safe to do so. Stop the leak. Turn leaking containers leak-side up to prevent the escape of liquid. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to disperse the vapors. Isolate area until gas has dispersed.
- Methods for cleaning up : Following product recovery, flush area with water. Clean thoroughly.

### 6.4. Reference to other sections

No additional information available

# Four Way Action N.C.

## Safety Data Sheet



### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Vapors may form explosive mixture with air. Exclude sources of heat, sparks and open flame. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any incandescent material. Do not smoke while handling product. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use only explosion-free electrical equipment with earth. Do not re-use empty containers. Obtain special instructions before use. Reduce/avoid exposure and/or contact. Do not breathe gas/vapor/aerosol. Avoid contact with skin, eyes and clothing. Avoid prolonged and repeated contact with skin. Use only outdoors or in a well-ventilated area. Wear recommended personal protective equipment.
- Hygiene measures : Wash thoroughly after handling. Use good personal hygiene practices.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Do not puncture, incinerate or crush. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Store locked up.
- Incompatible products : Refer to Section 10 on Incompatible Materials.
- Incompatible materials : Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.
- Storage area : Aerosol 3. Store in a cool area.
- Special rules on packaging : meet the legal requirements.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

| propane (74-98-6)   |                      |          |
|---|----------------------|----------|
| ACGIH   | ACGIH TWA (ppm)      | 1000 ppm |
| OSHA  | OSHA PEL (TWA) (ppm) | 1000 ppm |
| 2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether (112-34-5) |                      |          |
| ACGIH   | ACGIH TWA (ppm)      | 10 ppm   |

#### 8.2. Exposure controls

- Appropriate engineering controls : Provide sufficient air exchange and/or exhaust. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas.
- Personal protective equipment : Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Face shield. Protective clothing. Safety glasses.



- Hand protection : In case of repeated or prolonged contact wear gloves.
- Eye protection : Avoid contact with eyes. Face shield.
- Skin and body protection : Avoid contact with skin. Wear chemical protective equipment that is specifically recommended by the manufacturer. Use of an impervious apron is recommended. It may provide little or no thermal protection.
- Respiratory protection : If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
- Thermal hazard protection : Use appropriate personal protective equipment when risk assessment indicates this is necessary.
- Consumer exposure controls : When using do not smoke. Avoid contact with eyes. Avoid contact with skin. Keep away from food and drink. Use good personal hygiene practices. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash before reuse.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Aerosol. amber. dark brown.
- Odor : characteristic

# Four Way Action N.C.

## Safety Data Sheet



|   |                                |
|---|--------------------------------|
| Odor threshold                              | : No data available            |
| pH  | : No data available            |
| Melting point                               | : No data available            |
| Freezing point                              | : No data available            |
| Boiling point                               | : 182.69 °F estimated          |
| Flash point                                 | : -156 °F Propellant estimated |
| Relative evaporation rate (butyl acetate=1) | : No data available            |
| Flammability (solid, gas)                   | : No data available            |
| Explosion limits                            | : No data available            |
| Explosive properties                        | : No data available            |
| Oxidizing properties                        | : No data available            |
| Vapor pressure                              | : No data available            |
| Relative density                            | : No data available            |
| Relative vapor density at 20 °C             | : No data available            |
| Specific gravity / density                  | : 0.831 - 0.851 g/ml estimated |
| Solubility                                  | : No data available            |
| Log Pow                                     | : No data available            |
| Log Kow                                     | : No data available            |
| Auto-ignition temperature                   | : 254.99 °C estimated          |
| Decomposition temperature                   | : No data available            |
| Viscosity                                   | : No data available            |
| Viscosity, kinematic                        | : < 20 cSt                     |
| Viscosity, dynamic                          | : No data available            |

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

#### 10.2. Chemical stability

Risk of explosion. Risk of ignition. Unstable. The product is stable at normal handling- and storage conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

#### 10.4. Conditions to avoid

Heat. Open flame. Sparks. Incompatible materials. Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point.

#### 10.5. Incompatible materials

No additional information available

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Dermal: Not classified.

#### hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)

|                    |   |
|--------------------|---|
| LD50 dermal rabbit | > 5000 mg/kg body weight (Rabbit; Literature) |
|--------------------|---|

|  |                   |
|--|-------------------|
| Skin corrosion/irritation                          | : Not classified  |
| Serious eye damage/irritation                      | : Not classified. |
| Respiratory or skin sensitization                  | : Not classified  |
| Germ cell mutagenicity                             | : Not classified  |
| Carcinogenicity                                    | : Not classified. |
| Reproductive toxicity                              | : Not classified  |
| Specific target organ toxicity (single exposure)   | : Not classified  |
| Specific target organ toxicity (repeated exposure) | : Not classified  |

# Four Way Action N.C.

## Safety Data Sheet



|                                      |  |
|--------------------------------------|--|
| Aspiration hazard                    | : May be fatal if swallowed and enters airways.  |
| Symptoms/injuries after skin contact | : Contact during a long period may cause light irritation.   |
| Symptoms/injuries after eye contact  | : Direct contact with the eyes is likely irritating.   |
| Symptoms/injuries after ingestion    | : Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis. Risk of lung edema. |
| Likely routes of exposure            | : Skin and eyes contact.;Inhalation;Ingestion.   |

### SECTION 12: Ecological information

#### 12.1. Toxicity

|  |                           |
|--|---------------------------|
| hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8) |                           |
| LC50 fish 1  | > 100 mg/l (Pisces)       |
| EC50 Daphnia 1   | > 100 mg/l (Invertebrata) |
| Threshold limit algae 1  | > 100 mg/l (Algae)        |

#### 12.2. Persistence and degradability

|  |  |
|--|--|
| hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8) |  |
| Persistence and degradability  | Readily biodegradable in water. Adsorbs into the soil. |

#### 12.3. Bioaccumulative potential

|  |   |
|--|---|
| hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8) |   |
| Log Pow  | 6 - 8.2   |
| Bioaccumulative potential  | High potential for bioaccumulation (Log Kow > 5). |

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

|                         |  |
|-------------------------|--|
| Waste treatment methods | : Contents under pressure. Do not puncture, incinerate or crush. Do not allow into drains or water courses or dispose of where ground or surface waters may be affected. Dispose of contents/container to comply with local/regional/national/international regulations. |
| Additional information  | : This material and its container must be disposed of in a safe manner. Empty containers should be taken for recycle, recovery or waste in accordance with local regulation. Handle unclean empty containers as full ones.   |

### SECTION 14: Transport information

#### Department of Transportation (DOT)

|                                  |   |
|----------------------------------|---|
| Transport document description   | : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1 |
| UN-No.(DOT)                      | : UN1950  |
| Proper Shipping Name (DOT)       | : Aerosols<br>flammable, (each not exceeding 1 L capacity)            |
| Transport hazard class(es) (DOT) | : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115                      |
| Hazard labels (DOT)              | : 2.1 - Flammable gas   |



|  |  |
|--|--|
| DOT Packaging Non Bulk (49 CFR 173.xxx)                          | : None   |
| DOT Packaging Bulk (49 CFR 173.xxx)                              | : None   |
| DOT Special Provisions (49 CFR 172.102)                          | : N82  |
| DOT Packaging Exceptions (49 CFR 173.xxx)                        | : 306  |
| DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) | : 75 kg  |
| DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)     | : 150 kg   |
| DOT Vessel Stowage Location                                      | : A  |
| DOT Vessel Stowage Other   | : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials |

#### Additional information

|                   |   |
|-------------------|---|
| Other information | : This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.306. |
|-------------------|---|

# Four Way Action N.C.

## Safety Data Sheet



### ADR

No additional information available

### Transport by sea

UN-No. (IMDG) : UN1950  
 Proper Shipping Name (IMDG) : Aerosols  
 Class (IMDG) : 2.1 - Flammable gases  
 Limited quantities (IMDG) : LTD QTY

### Air transport

UN-No.(IATA) : UN1950  
 Proper Shipping Name (IATA) : Aerosols, flammable  
 Class (IATA) : 2.1 - Gases : Flammable

## SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

|   |
|---|
| propane (74-98-6)   |
| Not listed on SARA Section 313 (Specific toxic chemical listings) |
|   |

California Proposition 65 - This product does not contain substances known to the state of California to cause cancer and/or reproductive toxicity.

## SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

|                 |  |
|-----------------|--|
| Asp. Tox. 1     | Aspiration hazard Category 1                       |
| Carc. 1B        | Carcinogenicity Category 1B                        |
| Compressed gas  | Gases under pressure Compressed gas                |
| Eye Irrit. 2A   | Serious eye damage/eye irritation Category 2A      |
| Flam. Aerosol 1 | Flammable aerosol Category 1                       |
| Flam. Gas 1     | Flammable gases Category 1                         |
| Flam. Liq. 4    | Flammable liquids Category 4                       |
| H220            | Extremely flammable gas                            |
| H222            | Extremely flammable aerosol                        |
| H227            | Combustible liquid                                 |
| H280            | Contains gas under pressure; may explode if heated |
| H304            | May be fatal if swallowed and enters airways       |
| H319            | Causes serious eye irritation                      |
| H350            | May cause cancer                                   |

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.*