

PENETRATING OIL AEROSOL

Penetrant & Rust Preventative with PTFE Resin

Form: Liquid

Color: Colorless to Light Yellow

Odor: Solvent

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

VOC Content (% by weight): 81%

Flash Point (ASTM D-7821): 92°F

Specific Gravity: 1.00 g/cm³

Density: 8.35 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S. #

Trichloroethylene	79-01-6
Kerosene	8008-20-6
Heavy Paraffinic Petroleum Oil	64741-88-4
Aliphatic Petroleum Distillate.....	64742-89-8
Carbon Dioxide (Propellant).....	124-38-9

Great for...

- **Mechanics**
- **Pipefitters**
- **Plumbers**
- **Assemblers**
- **Maintenance personnel**

Provides Protection for...

- **Battery terminals**
- **Exhaust systems**
- **Rusted bolts**
- **Brake cables**
- **Pipe fittings**
- **Speedometer**
- **Electrical relays**
- **Parking meters**
- **Locks**
- **Rusted nuts**
- **Fuse boxes**
- **Anywhere a multipurpose lubricant is needed**

DIRECTIONS: Shake well before using. Hold nozzle 6 to 8 inches from corroded part. Saturate corroded area with PENETRATING OIL AEROSOL. Tap fitting lightly and allow several minutes to penetrate. Remove part. In some severe cases heating may be required.

HMIS				NFPA	
		Severe	4	Extreme	
Health	2	Serious	3	High	Health..... 2
Flammability	4	Moderate	2	Moderate	Flammability..... 4
Reactivity	0	Slight	1	Slight	Reactivity..... 0
Personal Protection.....	G	Minimal	0	Insignificant	Special Precautions..... None