



# GRAPHITE LUBRICANT

## GRAPHITE LUBRICANT SPRAY

### REDUCES FRICTION & HEAT

#### **DANGER:**

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.

May cause genetic defects. May cause cancer (Inhalation). May cause damage to organs through prolonged or repeated exposure.

#### **KEEP OUT OF REACH OF CHILDREN**

See back panel for further cautions and first aid instructions.

**NET WEIGHT:** 12 oz. (340 g)

**GRAPHITE LUBRICANT** lubricates and protects at the same time. It penetrates deeply to eliminate friction and squeaks and leaves a hard, dry, protective film of graphite. The no-mess **GRAPHITE LUBRICANT** film will not wash off and provides lubrication at high or low temperature extremes.



#### **DANGER:**

Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer (Inhalation). May cause damage to organs through prolonged or repeated exposure.

#### **PREVENTION:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, open flames, sparks. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe fume, gas, mist, spray, vapors. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash it before reuse.

#### **RESPONSE:**

**IF SWALLOWED:** Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting.

**IF ON SKIN:** Wash with plenty of water. **If skin irritation occurs:** Get medical advice/attention.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing.

**If exposed or concerned:** Get medical advice/attention. Call a doctor, a POISON CENTER if you feel unwell.

#### **STORAGE:**

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

#### **DISPOSAL:**

Dispose of contents/container to comply with local/regional/national/international regulations.

#### **INGREDIENTS/CAS#:**

Toluene (108-88-3); Propane (74-98-6); n-Butane (106-97-8); Graphite (7782-42-5); Acrylic Polymer(s) (Proprietary); Crystalline Silica (14808-60-7); Benzene (71-43-2); Ethylbenzene (100-41-4).

#### **NFPA® RATINGS:**

Health: 3; Flammability: 4; Reactivity: 0

#### **DIRECTIONS:**

Shake well before using. Hold nozzle 8 to 12 inches from the surface to be treated. Spray **GRAPHITE LUBRICANT** to cover surface with a light, even mist. For hard-to-reach areas, insert extension tube in spray tip. Clean the spray nozzle thoroughly after each use by inverting can and pressing valve for 2 to 3 seconds.

**Note:** Suitable for use with operating temperatures ranging from -100 °F. to +800 °F.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

#### **WARNING:**

This product can expose you to toluene, which is known to the State of California to cause birth defects or other reproductive harm. Crystalline Silica, which is known to the State of California to cause cancer, ethylbenzene, which is known to the State of California to cause cancer, and benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Sold by:

8211.050218

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • [www.sharecorp.com](http://www.sharecorp.com)