Safety Data Sheet



SECTION 1: Product and company identification

Product name : Spray Wax & CLeaner

Use of the substance/mixture : Aerosol

Cleaner

Product code : 821301

Company : Share Corporation

P.O. Box 245013

Milwaukee, WI 53224 - USA

T (414) 355-4000

Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222 Liquefied gas H280 Skin Irrit. 2 H315 Eye Irrit. 2A H319 Skin Sens. 1 H317 STOT SE 3 H336 Asp. Tox. 1 H304

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS02

 \Diamond





GHS04 GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Extremely flammable aerosol

Contains gas under pressure; may explode if heated May be fatal if swallowed and enters airways

Causes skin irritation

May cause an allergic skin reaction Causes serious eye irritation May cause drowsiness or dizziness

Precautionary statements (GHS-US)

Keep away from heat, sparks, open flames, hot surfaces, Do not smoke. - No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Avoid breathing mist, spray Wash thoroughly after handling

Use only outdoors or in a well-ventilated area

Contaminated work clothing must not be allowed out of the workplace

Wear protective gloves, eye protection

If swallowed: Immediately call a doctor, a POISON CENTER, Do NOT induce vomiting If on skin: Wash with plenty of IF ON SKIN: Wash with plenty of soap and water

If inhaled: Remove person to fresh air and keep comfortable for breathing

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

Call a PÓISON CENTER, a doctor if you feel unwell Specific treatment (see First aid measures on this label)

Do NOT induce vomiting

If skin irritation occurs: Get medical advice/attention
If skin irritation or rash occurs: Get medical advice/attention
If eye irritation persists: Get medical advice/attention
Take off contaminated clothing and wash before reuse
Take off contaminated clothing and wash it before reuse
Store in a well-ventilated place. Keep container tightly closed

Store locked up

Protect from sunlight. Store in a well-ventilated place

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Dispose of contents/container to comply with local/regional/national/international regulations

Date of issue: 9/15/2015 Revision date: 05/09/2015 Version: 1.0 P GHS SDS Page 1 of 6

Safety Data Sheet



2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Distillates (petroleum), light distillate hydrotreating process, low-boiling	(CAS No) 68410-97-9	25 - 35	Not classified
isobutane	(CAS No) 75-28-5	10 - 15	Not classified
propane	(CAS No) 74-98-6	1 - 5	Flam. Gas 1, H220 Compressed gas. H280

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation

: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or

doctor/physician if you feel unwell.

First-aid measures after skin contact

If skin irritation or rash occurs: Get medical advice/attention. Wash with plenty of soap and water.

Take off contaminated clothing and wash it before reuse.

First-aid measures after eye contact

: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue

rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion

Do not induce vomiting. Immediately call a poison center or doctor/physician. Vomiting: prevent

asphyxia/aspiration pneumonia.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries

 Extremely flammable. Contents under pressure. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.

Symptoms/injuries after inhalation

: Harmful if inhaled. Dizziness.

Symptoms/injuries after skin contact

Causes skin irritation.

Symptoms/injuries after eye contact Symptoms/injuries after ingestion : Causes serious eye irritation.

May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: Flammable aerosol. Under fire conditions closed containers may rupture or explode.

Explosion hazard

: Contains gas under pressure; may explode if heated. Vapors may travel long distances along ground before igniting/flashing back to vapor source. Bursting aerosol containers may be propelled from a

fire at high speed.

Reactivity : Upon combustion: CO and CO2 are formed.

5.3. Advice for firefighters

Firefighting instructions

: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. No action shall be taken involving any personal risk or without suitable training. Move containers away from the fire area if this can be done without risk.

Protection during firefighting : Do not attempt to take action without suitable protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures

Evacuate unnecessary personnel. Isolate from fire, if possible, without unnecessary risk. Gas is denser than air. May accumulate in low areas e.g. close to the ground. Eliminate every possible source of ignition.

6.1.1. For non-emergency personnel

Protective equipment

: Do not enter without an appropriate protective equipment.

Date of issue: 9/15/2015 Revision date: 05/09/2015 Version: 1.0 P GHS SDS Page 2 of 6

Safety Data Sheet

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Isolate area until gas has dispersed. Eliminate every possible source of

ignition. Use water spray to disperse the vapors. Collect spillage.

Methods for cleaning up : Take up liquid spill into inert absorbent material.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Do not puncture, incinerate or crush.

Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F.

Heat-ignition : KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.

Storage area : Store in a cool area. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propane (74-98-6)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	
isobutane (75-28-5)			
ACGIH	ACGIH STEL (ppm)	1000 ppm	

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Personal protective equipment : Gloves. Safety glasses. Insufficient ventilation: wear respiratory protection. Use appropriate personal

protective equipment when risk assessment indicates this is necessary.







SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance Aerosol. Liquid. Pleasant odor Odor Odor threshold No data available pН No data available Melting point : No data available Freezing point No data available **Boiling point** No data available Flash point : < 50 °F (liquid portion) Relative evaporation rate (butyl acetate=1) No data available Flammability (solid, gas) : No data available

Date of issue: 9/15/2015 Revision date: 05/09/2015 Version: 1.0 P GHS SDS Page 3 of 6



Safety Data Sheet

SHARE CORP

Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Vapor pressure : No data available
Relative density : No data available
Relative vapor density at 20 °C : No data available

Specific gravity / density : 0.9 g/ml

Solubility : Poorly soluble in water.

Log Pow : No data available

Log Kow : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity : No data available

Viscosity, kinematic : < 20 cSt

Viscosity, dynamic : No data available

VOC content : 45 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Upon combustion: CO and CO2 are formed.

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

No flames, No sparks. Eliminate all sources of ignition. Welding. Heat.

10.5. Incompatible materials

acids. Oxidizing agent.

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

 Skin corrosion/irritation
 : Causes skin irritation.

 Serious eye damage/irritation
 : Causes serious eye irritation.

 Respiratory or skin sensitization
 : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified. Reproductive toxicity : Not classified

 $\label{thm:continuous} \mbox{Specific target organ toxicity (single exposure)} \quad : \quad \mbox{May cause drowsiness or dizziness.}$

Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : May be fatal if swallowed and enters airways.

Symptoms/injuries after inhalation : Harmful if inhaled. Dizziness. Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

Likely routes of exposure : Dermal;Inhalation

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

Date of issue: 9/15/2015 Revision date: 05/09/2015 Version: 1.0 P GHS SDS Page 4 of 6

Safety Data Sheet



12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container to comply with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport hazard class(es) (DOT)

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1

UN-No.(DOT) : UN1950 Proper Shipping Name (DOT) : Aerosols

flammable, (each not exceeding 1 L capacity)
: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None DOT Packaging Bulk (49 CFR 173.xxx) : None DOT Special Provisions (49 CFR 172.102) : N82 DOT Packaging Exceptions (49 CFR : 306

173.xxx)

DOT Quantity Limitations Passenger : 75 kg

aircraft/rail (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft : 150 kg

only (49 CFR 175.75)

DOT Vessel Stowage Location : A

DOT Vessel Stowage Other : 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division

14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transpor

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

propane (74-98-6)

Not listed on SARA Section 313 (Specific toxic chemical listings)

California Proposition 65 - This product does not contain a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

Date of issue: 9/15/2015 Revision date: 05/09/2015 Version: 1.0 P GHS SDS Page 5 of 6

Safety Data Sheet



SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Asp. Tox. 1	Aspiration hazard Category 1	
Compressed gas	Gases under pressure Compressed gas	
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A	
Flam. Aerosol 1	Flammable aerosol Category 1	
Flam. Gas 1	Flammable gases Category 1	
Liquefied gas	Gases under pressure Liquefied gas	
Skin Irrit. 2	Skin corrosion/irritation Category 2	
Skin Sens. 1	Skin sensitization Category 1	
STOT SE 3	Specific target organ toxicity (single exposure) Category 3	
H220	Extremely flammable gas	
H222	Extremely flammable aerosol	
H280	Contains gas under pressure; may explode if heated	
H304	May be fatal if swallowed and enters airways	
H315	Causes skin irritation	
H317	May cause an allergic skin reaction	
H319	Causes serious eye irritation	
H336	May cause drowsiness or dizziness	


NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury

unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in

air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.

 Date of issue: 9/15/2015
 Revision date: 05/09/2015
 Version: 1.0
 P GHS SDS
 Page 6 of 6