



**FOR ALL GASOLINE & DIESEL ENGINES**  
EFFECTIVE TO -65°F

**DANGER**

**Extremely Flammable Aerosol**

Extremely flammable liquid and vapor. Contains gas under pressure; may explode if heated. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness. May cause cancer.

**KEEP OUT OF REACH OF CHILDREN**

**CONTENTS UNDER PRESSURE.**

See additional cautions on back panel.

**NET WEIGHT:** 11 oz (312 g)

**STARTING FLUID** is designed to provide quick starts for all engines in extreme cold or damp weather. Its lubricants protect engines from corrosion while preserving batteries and ignition systems by minimizing cranking time. **STARTING FLUID** is designed for use on 2- and 4-cycle engines that use either gasoline or diesel fuel, and is effective down to -65°F.



**DANGER:**

Extremely flammable aerosol. Extremely flammable liquid and vapor. Contains gas under pressure; may explode if heated. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness. May cause cancer.

**PREVENTION:**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, hot surfaces. Do not smoke. - No smoking. Do not spray on an open flame or other ignition source. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, lighting, ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Pressurized container; Do not pierce or burn, even after use. Avoid breathing fume, vapors, spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, eye protection. Take off contaminated clothing and wash it before reuse.

**RESPONSE:**

**IF SWALLOWED:** Immediately call a doctor, a POISON CENTER. Do NOT induce vomiting. Rinse mouth.

**IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water/shower.

**If skin irritation occurs:** Get medical advice/attention.

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing.

**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **If eye irritation persists:** Get medical advice/attention.

**If exposed or concerned:** Get medical advice/attention. Call a doctor, a POISON CENTER if you feel unwell.

**In case of fire:** Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish.

**STORAGE:**

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122 °F.

**DISPOSAL:**

Dispose of contents/container to comply with local/regional/national/international regulations.

**INGREDIENTS/CAS#:**

Heptane/142-82-5; Diethyl Ether/60-29-7; Heavy Hydrotreated Naphthenic Distillates /64742-52-5; Carbon Dioxide/124-38-9

**NFPA® RATINGS:**

Health: 2; Flammability: 4; Reactivity: 0

**DIRECTIONS:**

Do not flood engine before using. Spray **STARTING FLUID** into air cleaner or carburetor once for 2 to 3 seconds. Stand clear because carburetor can backfire. Try starting engine in normal manner. If engine doesn't start repeat above procedure up to three more times. If engine still fails to start, ignition should be checked by a professional.

**NOTE:** Avoid contact with battery terminals, solenoid, or other electrical components. Never spray while ignition is in "ON" position. Avoid overuse of product. Do not smoke while using product.

This diesel fuel additive complies with the Federal low sulfur content requirements for use in diesel motor vehicles and non-road engines.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

Sold by:

8550.051515