

PAINT STRIPPER AEROSOL

Paint & Varnish Remover Spray

Form:

Color:

Odor:

pH: 12.5-13.4

Solubility (in water): Yes

Flash Point (ASTM D-7821): -156°F

Specific Gravity: 0.765 g/mL

Density: 6.38 lbs/gal

Storage Stability (at 70°F): 1 year

This Product Contains: **CAS#**

Toluene	108-88-3
Propane	74-98-6
Butoxyethanol	111-76-2
Acetone	67-64-1
Butane	106-97-8
Diethylene Glycol Monobutyl Ether	112-34-5
Sodium Hydroxide	1310-73-2

Great For Use As...

- Concrete Seal Remover
- Gasket Remover
- Graffiti Remover
- Gym Floor Stripper

Safe On...

- Iron
- Steel
- Brass
- Brick
- Concrete
- Wood
- Aluminum

Directions for Use: Spray PAINT REMOVER AEROSOL uniformly over the surface to be stripped. Allow product to penetrate and soften paint for 5-15 minutes. On thicker paint, a second application may be required. Remove softened paint with scrapper, putty knife, cloth or strong water spray. PAINT STRIPPER AEROSOL is also water flushable. Wipe the treated surface and allow to dry before repainting.

CONSULT PRODUCT LABEL FOR DETAILED DIRECTIONS

HMIS				NFPA	
		Severe	4	Extreme	
Health.....	3	Serious	3	High	Health.....
Flammability.....	3	Moderate	2	Moderate	Flammability.....
Reactivity.....	1	Slight	1	Slight	Reactivity.....
Personal Protection.....	X	Minimal	0	Insignificant	Special Precautions.....
					None