

# High Solids Industrial Strength Spray Paint Aluminum

## Safety Data Sheet



### SECTION 1: Product and company identification

Product name : High Solids Industrial Strength Spray Paint Aluminum  
Use of the substance/mixture : Paint  
Coating  
Product code : 883001  
Company : Share Corporation  
P.O. Box 245013  
Milwaukee, WI 53224 - USA  
T (414) 355-4000  
[sharecorp.com](http://sharecorp.com)  
Emergency number : For Chemical Emergency Call Chemtrec 24hr/day 7days/week: 1-800-424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

GHS-US classification  
Flam. Aerosol 1 H222  
Press. Gas (Liq.) H280  
Skin Irrit. 2 H315  
Repr. 1 H360  
STOT SE 3 H336  
STOT RE 2 H373

#### 2.2. Label elements

GHS US labelling

Hazard pictograms (GHS US)



GHS02

GHS04

GHS07

GHS08

Signal word (GHS US)

: Danger

Hazard statements (GHS US)

: Extremely flammable aerosol  
Contains gas under pressure; may explode if heated  
Causes skin irritation  
May cause drowsiness or dizziness  
May damage fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure  
Precautionary statements (GHS US) : Obtain special instructions before use.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.  
Do not breathe dust, fume, gas, mist, vapours, spray.  
Wash hands thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
If inhaled: Remove person to fresh air and keep comfortable for breathing.  
Call a poison center or doctor if you feel unwell.  
Specific treatment (see supplemental first aid instruction on this label).  
Take off contaminated clothing and wash it before reuse.  
Store in a well-ventilated place.  
Store locked up.  
Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).  
Dispose of container, contents to comply with local/regional/national/international regulations.

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

# High Solids Industrial Strength Spray Paint

## Aluminum

### Safety Data Sheet



#### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Acetone	(CAS-No.) 67-64-1	10 - 30*	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Toluene	(CAS-No.) 108-88-3	10 - 30*	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Hydrotreated Light Alkanes (Solvent)	(CAS-No.) 64742-47-8	5 - 10*	Flam. Liq. 4, H227 Asp. Tox. 1, H304

All hazardous chemicals, as determined by 29 CFR 1910.1200 have been listed. A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures general : Call a poison center or a doctor if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : May cause drowsiness or dizziness.
- Symptoms/effects after inhalation : May cause drowsiness or dizziness.
- Symptoms/effects after skin contact : None under normal conditions. Contact with the liquefied gas may cause frostbite.
- Symptoms/effects after eye contact : May cause eye irritation. Eye irritation.
- Symptoms/effects after ingestion : May cause irritation to the digestive tract.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS THE LEAK CAN BE STOPPED. Dry chemical, CO<sub>2</sub>, or water spray or regular foam. Water spray. Dry powder. Foam.
- Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Pressurised container: May burst if heated. Heating may cause a fire or explosion.
- Explosion hazard : Explosion risk in case of fire. Heating may cause an explosion.
- Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

### 5.3. Advice for firefighters

- Precautionary measures fire : Keep container tightly closed and away from heat, sparks and flame.
- Firefighting instructions : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection.
- Protection during firefighting : Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.

# High Solids Industrial Strength Spray Paint Aluminum

## Safety Data Sheet



### 6.1.1. For non-emergency personnel

- Protective equipment : Wear recommended personal protective equipment.
- Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so.

### 6.2. Environmental precautions

Avoid release to the environment. Avoid discharge to atmosphere.

### 6.3. Methods and material for containment and cleaning up

- For containment : Stop leak without risks if possible.
- Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Obtain special instructions before use. Use only outdoors or in a well-ventilated area. Prevent the build-up of electrostatic charge. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Use only non-sparking tools. Ground/bond container and receiving equipment.
- Storage conditions : Protect from sunlight. Store in a well-ventilated place. Keep only in original container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in fireproof place. Keep container closed when not in use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Keep container tightly closed.
- Packaging materials : Store always product in container of same material as original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Acetone (67-64-1)		
ACGIH	ACGIH OEL TWA	594 mg/m <sup>3</sup>
ACGIH	ACGIH OEL TWA	250 ppm
ACGIH	ACGIH OEL STEL	1187 mg/m <sup>3</sup>
ACGIH	ACGIH OEL STEL	500 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
OSHA	OSHA PEL TWA	2400 mg/m <sup>3</sup>
OSHA	OSHA PEL TWA	1000 ppm
Toluene (108-88-3)		
ACGIH	ACGIH OEL TWA	20 ppm
ACGIH	Remark (ACGIH)	Visual impair; female repro; pregnancy loss; A4; BEI
OSHA	OSHA PEL TWA	200 ppm
OSHA	OSHA PEL C	300 ppm
Hydrotreated Light Alkanes (64742-47-8)		
Not applicable		

### 8.2. Exposure controls

- Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.

# High Solids Industrial Strength Spray Paint Aluminum

## Safety Data Sheet



Personal protective equipment : Wear recommended personal protective equipment. Gloves. Safety glasses. Protective clothing.



Hand protection : Protective gloves.  
Eye protection : Safety glasses.  
Skin and body protection : Wear suitable protective clothing.  
Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.  
Environmental exposure controls : Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Gas  
Appearance : Aerosol  
Odour : aromatic  
Odour threshold : No data available  
pH : No data available  
Melting point : No data available  
Freezing point : No data available  
Boiling point : -44 °C  
Flash point : -19 °C  
Relative evaporation rate (butylacetate=1) : No data available  
Flammability : No data available  
Explosive limits : No data available  
Explosive properties : No data available  
Oxidising properties : No data available  
Vapour pressure : No data available  
Relative density : No data available  
Relative vapour density at 20°C : No data available  
Density : 0.77 – 0.85 g/ml  
Solubility : No data available  
Partition coefficient n-octanol/water (Log Pow) : No data available  
Partition coefficient n-octanol/water (Log Kow) : No data available  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Viscosity : No data available  
Viscosity, kinematic : No data available  
Viscosity, dynamic : No data available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Extremely flammable aerosol. Pressurised container: May burst if heated.

### 10.3. Possibility of hazardous reactions

May mass explode in fire. Heating may cause a fire or explosion.

### 10.4. Conditions to avoid

High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5. Incompatible materials

Combustible materials.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# High Solids Industrial Strength Spray Paint Aluminum

## Safety Data Sheet



### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

##### Hydrotreated Light Alkanes (64742-47-8)

LD50 oral rat	> 15000 mg/kg Source: IUCLID
LD50 dermal rabbit	> 2000 mg/kg Source: IUCLID
LC50 Inhalation - Rat	> 5.28 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), 95% CL: 0,42 -

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Not classified.  
Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified.  
Carcinogenicity : Not classified.

##### Toluene (108-88-3)

IARC group 3 - Not classifiable

Reproductive toxicity : May damage fertility or the unborn child.  
STOT-single exposure : May cause drowsiness or dizziness.  
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

##### Hydrotreated Light Alkanes (64742-47-8)

NOAEL (oral, rat, 90 days)	750 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	≥ 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Aspiration hazard : Not applicable  
Symptoms/effects after inhalation : May cause drowsiness or dizziness.  
Symptoms/effects after skin contact : None under normal conditions. Contact with the liquefied gas may cause frostbite.  
Symptoms/effects after eye contact : May cause eye irritation. Eye irritation.  
Symptoms/effects after ingestion : May cause irritation to the digestive tract.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

##### Hydrotreated Light Alkanes (64742-47-8)

LC50 - Fish [1] 2.4 mg/l Source: ECOTOX

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

##### Hydrotreated Light Alkanes (64742-47-8)

Partition coefficient n-octanol/water (Log Pow) 3.3 – 6 Source: IUCLID

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.  
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Sewage disposal recommendations : Disposal must be done according to official regulations.  
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.  
Additional information : Do not re-use empty containers.

# High Solids Industrial Strength Spray Paint Aluminum

## Safety Data Sheet



### SECTION 14: Transport information

#### Department of Transportation (DOT)

Transport document description (DOT) : UN1950 Aerosols, flammable, n.o.s., 2.1  
UN-No. (DOT) : UN1950  
Proper Shipping Name (DOT) : Aerosols, flammable, n.o.s.  
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115  
Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : 304  
DOT Special Provisions (49 CFR 172.102) : N82  
DOT Packaging Exceptions (49 CFR 173.xxx) : 306  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg  
DOT Vessel Stowage Location : A  
DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

#### Additional information

Other information : No supplementary information available.

#### ADR

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

#### Acetone (67-64-1)

CERCLA RQ : 5000 lb

#### Toluene (108-88-3)

Listed on EPA Hazardous Air Pollutant (HAPS)


CERCLA RQ : 1000 lb

#### WARNING

This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### SECTION 16: Other information

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.  
NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.  
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



# High Solids Industrial Strength Spray Paint Aluminum

## Safety Data Sheet



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.