



# HIGH SOLIDS

## INDUSTRIAL STRENGTH



ENAMEL  
FLAT BLACK

- Maximum Coverage
- Maximum Strength & Durability
- Maximum Protection Against Rust and Chemicals

**KEEP OUT OF REACH OF CHILDREN**

**DANGER! EXTREMELY FLAMMABLE LIQUID AND VAPOR.**  
VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE.  
VAPOR HARMFUL. SEE OTHER CAUTIONS ON BACK PANEL.

**NET WEIGHT: 16 OZ (454 g)**



# HIGH SOLIDS

## INDUSTRIAL STRENGTH



**DANGER!** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

**Prevention:** Pressurized container; do not pierce or burn, even after use. Use only with adequate ventilation. Do not breathe dust/vapors/spray mist. Avoid contact with eye/skin/clothing. Wear protective gloves/clothing/glasses. Keep away from heat/sparks/open flames/hot surfaces. Do not eat/drink/smoke when using this product. Do not spray on naked flame or other ignition sources.

**Response:** In case of fire, use extinguishing powder or water spray. Immediately contact a doctor or POISON CONTROL CENTER if you feel unwell. If medical attention is needed, have product label at hand.

**IF IN EYES:** Rinse with water for several minutes. Remove contact lenses if present.

**If eye irritation persists:** Seek medical attention.

**IF SWALLOWED:** Rinse mouth with water. Do not induce vomiting.

**IF INHALED:** Remove to fresh air.

**IF ON SKIN:** Wash thoroughly with water. Remove all contaminated clothing.

**Storage:** Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C to 122°F.

**Disposal:** Dispose of product in accordance with local/regional/national/international regulations.

**Additional Precaution Statements:** Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. In cases where short and/or long term overexposure conditions exist, a charcoal filter respirator should be worn. Follow respirator manufacturer's directions for use.

### DIRECTIONS:

1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C).
2. Shake can at least 1 minute after rattle is heard and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10" (20 to 25cm). Several light coats give a better finish than one heavy coat. Recoat - For best results, recoat within one hour or after 48 hours. *This time varies with curing temperature, humidity, and film thickness. Test a small hidden area before recoating.*
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

### INGREDIENTS/CAS#:

Acetone (67-64-1), Propane (74-98-6), Calcium Carbonate (1317-65-3), N-Butane (106-97-8), Isobutyl Acetate (110-19-0), VM&P Naphtha (64742-89-8), PM Acetate (108-65-6), Glycol Ether EP (2807-30-9), Methyl Isobutyl Ketone (108-10-1), Methyl Propyl Ketone (107-87-9), Silicon Dioxide (112926-00-8). OTHER INGREDIENTS: (Contents partially unknown) Soya Alkyd Resin.

**WARNING:** This product can expose you to chemicals including Methyl isobutyl ketone, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

8833.010924

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • [www.sharecorp.com](http://www.sharecorp.com)