

High Solids Industrial Strength Spray Paint Pro Blue

Safety Data Sheet



SECTION 1: Product and company identification

Product name : High Solids Industrial Strength Spray Paint Pro Blue
Use of the substance/mixture : Paint
Coating
Product code : 883501
Company : Share Corporation
P.O. Box 245013
Milwaukee, WI 53224 - USA
T (414) 355-4000
sharecorp.com
Emergency number : For Chemical Emergency Call Chemtrec 24hr/day 7days/week: 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification
Aerosol 1 H222;H229
Eye Irrit. 2A H319
Carc. 2 H351
STOT SE 3 H336
STOT RE 2 H373

2.2. Label elements

GHS US labelling
Hazard pictograms (GHS US) :



GHS02 GHS07 GHS08

Signal word (GHS US) :
Hazard statements (GHS US) :

: Danger
: Extremely flammable aerosol
Pressurized container; may burst if heated
Causes serious eye irritation
May cause drowsiness or dizziness
Suspected of causing cancer.
May cause damage to organs through prolonged or repeated exposure
: Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Do not breathe dust, fume, gas, mist, vapours, spray.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear eye protection, protective gloves, protective clothing, face protection.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
Call a poison center or doctor if you feel unwell.
Get medical advice or attention if you feel unwell.
If eye irritation persists: Get medical advice or attention.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
Dispose of contents and container to comply with local/regional/national/international regulations.

Precautionary statements (GHS US) :

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable.

High Solids Industrial Strength Spray Paint Pro Blue

Safety Data Sheet



SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Acetone	(CAS-No.) 67-64-1	10 - 30*	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Propoxyethanol	(CAS-No.) 2807-30-9	5 - 10*	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Eye Irrit. 2A, H319
Titanium Oxide (Contaminant, By-product)	(CAS-No.) 13463-67-7	1 - 5*	Carc. 2, H351
Butyl Acetate	(CAS-No.) 123-86-4	1 - 5*	Flam. Liq. 3, H226 STOT SE 3, H336

All hazardous chemicals, as determined by 29 CFR 1910.1200 have been listed. A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Suspected of causing cancer.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Wash skin with plenty of water. Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness. Causes damage to organs.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: None under normal conditions. Contact with the liquefied gas may cause frostbite.
Symptoms/effects after eye contact	: May cause eye irritation. Eye irritation. Causes serious eye irritation.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS THE LEAK CAN BE STOPPED. Dry chemical, CO ₂ , or water spray or regular foam. Water spray. Dry powder. Foam. Carbon dioxide. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol. Pressurised container: May burst if heated. Heating may cause a fire or explosion.
Explosion hazard	: Explosion risk in case of fire. Heating may cause an explosion.
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

Precautionary measures fire	: Keep container tightly closed and away from heat, sparks and flame.
-----------------------------	---

High Solids Industrial Strength Spray Paint Pro Blue

Safety Data Sheet



- | | |
|--------------------------------|--|
| Firefighting instructions | : Eliminate all ignition sources if safe to do so. Fight fire remotely due to the risk of explosion. Do not enter fire area without proper protective equipment, including respiratory protection. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. |
| Protection during firefighting | : Self-contained breathing apparatus. Do not attempt to take action without suitable protective equipment. Complete protective clothing. Do not enter fire area without proper protective equipment, including respiratory protection. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- | | |
|------------------|--|
| General measures | : Eliminate every possible source of ignition. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage. |
|------------------|--|

6.1.1. For non-emergency personnel

- | | |
|----------------------|---|
| Protective equipment | : Wear recommended personal protective equipment. |
| Emergency procedures | : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Evacuate unnecessary personnel. |

6.1.2. For emergency responders

- | | |
|----------------------|--|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapours/spray. |
| Emergency procedures | : Evacuate unnecessary personnel. Stop leak if safe to do so. Ventilate area. |

6.2. Environmental precautions

Avoid release to the environment. Avoid discharge to atmosphere. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- | | |
|-------------------------|--|
| For containment | : Stop leak without risks if possible. |
| Methods for cleaning up | : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. |
| Other information | : Dispose of materials or solid residues at an authorized site. |

6.4. Reference to other sections

For further information refer to section 13. See Section 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- | | |
|-----------------------------------|---|
| Additional hazards when processed | : Not expected to present a significant hazard under anticipated conditions of normal use. |
| Precautions for safe handling | : Obtain special instructions before use. Use only outdoors or in a well-ventilated area. Prevent the build-up of electrostatic charge. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Wash thoroughly after handling. |

7.2. Conditions for safe storage, including any incompatibilities

- | | |
|------------------------|---|
| Technical measures | : Use only non-sparking tools. Ground/bond container and receiving equipment. |
| Storage conditions | : Protect from sunlight. Store in a well-ventilated place. Keep only in original container. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep in fireproof place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Keep container tightly closed. Keep only in the original container in a cool, well ventilated place away from : |
| Incompatible products | : Strong bases. Strong acids. |
| Incompatible materials | : Sources of ignition. Direct sunlight. |
| Packaging materials | : Store always product in container of same material as original container. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Acetone (67-64-1)

ACGIH	ACGIH OEL TWA	594 mg/m ³
-------	---------------	-----------------------

High Solids Industrial Strength Spray Paint Pro Blue

Safety Data Sheet



ACGIH	ACGIH OEL TWA	250 ppm
ACGIH	ACGIH OEL STEL	1187 mg/m ³
ACGIH	ACGIH OEL STEL	500 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
OSHA	OSHA PEL TWA	2400 mg/m ³
OSHA	OSHA PEL TWA	1000 ppm

Propoxyethanol (2807-30-9)

Not applicable

Titanium Oxide (13463-67-7)

ACGIH	ACGIH OEL TWA	0.2 mg/m ³ (Nanoscale particles. R - Repirable particulate matter) 2.5 mg/m ³ (Finescale particles. R - Repirable particulate matter)
ACGIH	Remark (ACGIH)	TLV® Basis: LRT irr; pneumoconiosis. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
OSHA	OSHA PEL TWA	15 mg/m ³

Butyl Acetate (123-86-4)

ACGIH	ACGIH OEL TWA	150 ppm
ACGIH	ACGIH OEL STEL	200 ppm
ACGIH	Remark (ACGIH)	Eye & URT irr
OSHA	OSHA PEL TWA	710 mg/m ³
OSHA	OSHA PEL TWA	150 ppm

8.2. Exposure controls

Appropriate engineering controls
Personal protective equipment

- : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.
- : Wear recommended personal protective equipment. Gloves. Safety glasses. Protective clothing. Avoid all unnecessary exposure.



Hand protection

Eye protection

Skin and body protection

Respiratory protection

- : Protective gloves. Wear protective gloves.
- : Safety glasses. Chemical goggles or safety glasses.
- : Wear suitable protective clothing.
- : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.

Environmental exposure controls

Other information

- : Avoid release to the environment.
- : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol
Odour	: aromatic
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: -44 °C
Flash point	: -19 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

High Solids Industrial Strength Spray Paint Pro Blue

Safety Data Sheet



Vapour pressure	: No data available
Relative density	: No data available
Relative vapour density at 20°C	: No data available
Density	: 0.77 – 0.85 g/ml
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Partition coefficient n-octanol/water (Log Kow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Extremely flammable aerosol. Pressurised container: May burst if heated. Not established.

10.3. Possibility of hazardous reactions

May mass explode in fire. Heating may cause a fire or explosion. Not established.

10.4. Conditions to avoid

High temperature. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Combustible materials. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Propoxyethanol (2807-30-9)

ATE CLP (dermal)	1100 mg/kg bodyweight
------------------	-----------------------

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

Titanium Oxide (13463-67-7)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.

STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
------------------------	--

Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects after inhalation	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: None under normal conditions. Contact with the liquefied gas may cause frostbite.
Symptoms/effects after eye contact	: May cause eye irritation. Eye irritation. Causes serious eye irritation.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract.

High Solids Industrial Strength Spray Paint Pro Blue

Safety Data Sheet



SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

High Solids Industrial Strength Spray Paint Pro Blue

Persistence and degradability : Not established.

12.3. Bioaccumulative potential

High Solids Industrial Strength Spray Paint Pro Blue

Bioaccumulative potential : Not established.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations : Disposal must be done according to official regulations.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
Additional information : Do not re-use empty containers.
Ecological waste information : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description (DOT) : UN1950 Aerosols, flammable, n.o.s., 2.1
UN-No. (DOT) : UN1950
Proper Shipping Name (DOT) : Aerosols, flammable, n.o.s.
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : 304
DOT Special Provisions (49 CFR 172.102) : N82
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A
DOT Vessel Stowage Other : 25 - Protected from sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

High Solids Industrial Strength Spray Paint Pro Blue

Safety Data Sheet



SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Acetone (67-64-1)

CERCLA RQ	5000 lb
-----------	---------

Butyl Acetate (123-86-4)

CERCLA RQ	5000 lb
-----------	---------

WARNING

This product can expose you to chemicals including Methyl isobutyl ketone, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


SECTION 16: Other information

Other information : None.

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.