



SPECIMEN LABEL

MOLY LUBE

INSTANT LUBRICATION

FAST DRYING

WITHSTANDS HIGH TEMPERATURE AND EXTREME PRESSURE.

EFFECTIVE UP TO 1000°F.

FOR INDUSTRIAL/PROFESSIONAL USE ONLY. NOT FOR RETAIL SALE.

DANGER: EXTREMELY FLAMMABLE
VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED
CONTENTS UNDER PRESSURE. KEEP OUT OF REACH OF CHILDREN
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONS.

Si usted no entiende la etiqueta, busque a alguien para que se la explique a usted en detalle.
(If you do not understand this label, find someone to explain it to you in detail.)

Net Weight: 11 oz. (312 g)

MOLY LUBE provides instant lubrication under extreme conditions. It quickly dries to a hard, black coating of molybdenum disulfide and adheres to most substrates, especially metal, with minimal surface preparation. **MOLY LUBE** resists wear and abrasion under extreme pressures and temperatures. Unlike many other lubricants, the **MOLY LUBE** lubricating film dries completely and will not attract dirt or dust. Ideal for chain lubrication, maintenance on furnaces, kilns, ovens, conveyors, gaskets, anti-seize and mold release applications.



DANGER:

KEEP OUT OF REACH OF CHILDREN. READ LABEL AND SDS BEFORE USE. EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. MAY CAUSE DROWSINESS OR DIZZINESS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION.

PREVENTION:

Avoid breathing mist/spray. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Do not spray on open flame or other ignition source. Pressurized container; do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear protective gloves. Wear eye protection.

RESPONSE:

IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation occurs: Get medical attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

STORAGE:

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up.

DISPOSAL:

Dispose of contents and container in accordance with all local, regional, and national regulations.

INGREDIENTS/CAS#:

Liquefied Petroleum Gas (68476-86-8), Acetone (67-64-1), Methyl Acetate (79-20-9), Isopropyl Alcohol (67-63-0), Molybdenum Disulfide (1317-33-5).

HMIS RATINGS:

Health: 2; Flammability: 4; Reactivity: 0; Personal Protection: G

DIRECTIONS:

Shake well before using. Clean surface thoroughly. Hold can 6 to 8 inches from surface and apply even, thin layer coats. Allow 1 to 5 minutes for adequate drying. The concentration of solids in this product may clog nozzle. Shake vigorously and often. Before starting, turn can upside down and spray until nozzle is clear.

This product is designed exclusively for industrial and institutional use by trained personnel. This product is sold 'as is' and the manufacturer makes no warranty, expressed or implied, or merchantability, and/or fitness for a particular purpose or otherwise. 480118L4292.112921

KEEP OUT OF REACH OF CHILDREN

Refer to SDS for further information.

Sold by:

8227.110221



Please Recycle.